



CENOVNIK VIDEO NADZORA I PRATEĆE OPREME

Važi od: 22.10.2018



HIKVISION



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
<u>DS-7104HQHI-K1</u> 	5003	4-KANALNI TURBO HD SNIMAČ (ANALOG + HDTVI + IP + AHD) -Rezolucija snimanja: 4Mpx lite@15fps, 1080p lite/720p/4CIF@25fps, 3 MP/1080p/720p@15fps, 1080p/720p@15fps, 720p/WD1/4CIF@25fps -Rezolucija snimanja 2 IP kamere: do 6 megapiskela -Video kompresija: H.265+/H.265/H.264+/H.264 video kompresija, -Video/audio ulazi: 4ch BNC, 1ch audio -Video/audio izlazi: HDMI/VGA (1920X1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz), 1-ch audio, RCA (2.0 Vp-p, 1 kΩ) (koristi audio ulaz) -Dodatni ulazi: RJ45 mrežni ulaz, 2 USB 2.0 interfejs -Mrežni protokoli: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF -Hard disk prostor: 1 sata HDD do 6TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Radna temperatura -10 °C ~ +55 °C, Dimenzije 200 × 200 × 45mm, Težina 1Kg	91,20	76,00
<u>DS-7204HQHI-K1</u> 	4918	4-KANALNI TURBO HD TRIBRID (ANALOG + HDTVI + IP + AHD) -Rezolucija snimanja: 4Mpx lite@15fps, 1080p lite/720p/4CIF@25fps, 3 MP/1080p/720p@15fps, 1080p/720p@15fps, 720p/WD1/4CIF@25fps -Rezolucija snimanja 2 IP kamere: do 6 megapiskela -Video/audio ulazi: H.265+/ H.265/ H.264+/ H.264 video kompresija, 4ch BNC, 1ch audio -Video/audio izlazi: CVBS, HDMI/VGA (1920X1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz), 1-ch audio, RCA (2.0 Vp-p, 1 kΩ) -Dodatni ulazi: RJ45 mrežni ulaz, RS-485, 2 x USB 2.0 interfejs, -Mrežni protokoli: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF -Hard disk prostor: 1 sata HDD do 10TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 6W bez HDD, Rad.temp. -10 °C ~+55 °C, Dimenzije 315 × 242 × 45mm, Težina 1,16Kg	107,16	89,30
<u>DS-7204HUHI-K1</u> 	5391	4-KANALNI TURBO HD HIBRID (ANALOG + AHD + HDTVI + IP) -Rezolucija snimanja: 12fps@5MP, 15fps@4MP, 18fps@3MP, 25fps@1080P... -Rezolucija snimanja IP kamere: do 8 megapiskela rezolucije -Video/audio ulazi: H.265+/H.265/H.264+/H.264 video kompresija, 4ch BNC, 1ch audio -Video/audio izlazi: HDMI/VGA/CVBS (1920X1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz), 1-ch audio -Dodatni ulazi: RJ45 mrežni ulaz, Alarmni ulazi / izlazi 4/1, RS-485, 2xUSB 2.0 -Mrežni protokoli: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF -Hard disk prostor: 1 sata HDD do 10TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 10W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 315×242×45mm, Težina 1,16Kg	142,80	119,00

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
DS-7108HQHI-K1				
	5004	8-KANALNI TURBO HD SNIMAČ (ANALOG + HDTVI + IP + AHD) -Rezolucija snimanja: 4Mpx lite@15fps, 1080p lite/720p/4CIF@25fps, 3 MP/1080p/720p@15fps, 1080p/720p@15fps, 720p/WD1/4CIF@25fps -Rezolucija snimanja 4 IP kamere: do 6 megapiksela rezolucije -Video kompresija: H.265+/H.265/H.264+/H.264 video kompresija, -Video/audio ulazi: 8ch BNC, 1ch audio -Video/audio izlazi: HDMI/VGA (1920X1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz), 1-ch audio, RCA (2.0 Vp-p, 1 kΩ) (koristi audio ulaz) -Dodatni ulazi: RJ45 mrežni ulaz, 2 USB 2.0 interfejs -Mrežni protokoli: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF -Hard disk prostor: 1 sata HDD do 6TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 200×200×45mm, Težina 1Kg	138,00	115,00
DS-7208HQHI-K2				
	4925	8-KANALNI TURBO HD TRIBRID (ANALOG + HDTVI + AHD + IP) -Rezolucija snimanja: 4Mpx lite@15fps, 1080p lite/720p/4CIF@25fps, 3 MP/1080p/720p@15fps, 1080p/720p@15fps, 720p/WD1/4CIF@25fps -Rezolucija snimanja 4 IP kamere: do 6 megapiksela -Video/audio ulazi: H.265 Pro+/H.265 Pro/H.265+/ H.265/ H.264+ / H.264 video kompresija, 8ch BNC, 1ch audio -Video/audio izlazi: CVBS, HDMI/VGA (1920X1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz), 1-ch audio, RCA (1 kΩ) -Dodatni ulazi: RJ45 mrežni ulaz, RS-485, 2 xUSB 2.0 interfejs, -Mrežni protokoli: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF -Hard disk prostor: 2 sata HDD do 10TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 7,5W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 380×320×48mm, Težina 1,78Kg	192,00	160,00
DS-7208HUHI-K2				
 	5440	8-KANALNI TURBO HD HIBRID (ANALOG + AHD + HDTVI + IP) -Rezolucija snimanja: 8 MP@8fps/5 MP@12fps/4 MP@15fps/3 MP@18fps 1080p/720p...@25fps -Rezolucija snimanja 8 IP kamera: do 8 megapiksela rezolucije -Video/audio ulazi: H.265 Pro+/H.265 Pro/H.265+/H.264+/H.264 video kompresija, 8ch BNC, 4ch audio, CVBS -Video/audio izlazi: HDMI (4K 3840X2160/30Hz, 2K 2560x1440/60Hz...), VGA (1920×1080/60H...), 1-ch audio -Dodatni ulazi: RJ45 mrežni ulaz, Alarmni ulazi / izlazi 8/4, RS-485, 1 USB 2.0 interfejs, 1 USB 3.0 -Mrežni protokoli: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF -Hard disk prostor: 2 sata HDD do 10TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 10W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 380×320×48mm, Težina 1,16Kg	266,40	222,00
4K ULTRA HD				

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
<u>DS-7116HQHI-K1</u>		16-KANALNI TURBO HD (ANALOG + HDTVI + IP + AHD) -Rezolucija snimanja: 4Mpx lite @15fps, 1080p lite /720p/4CIF@25fps, 3 MP/1080p/720p@15fps, 1080p/720p@15fps, 720p/WD1/4CIF@25fps -Rezolucija snimanja 8 IP kamera: do 6 megapiksela rezolucije -Video kompresija: H.265 Pro+/H.265 Pro/H.265+/H.265/H.264+/H.264 -Video/audio ulazi: 16ch BNC, 1ch audio -Video/audio izlazi: HDMI 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz..., VGA (1920 × 1080/60Hz...), 1-ch audio, RCA (2.0 Vp-p, 1 kΩ) -Dodatni ulazi: RJ45 mrežni ulaz, RS-485, 2 USB 2.0 interfejs, -Mrežni protokoli: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF -Hard disk prostor: 1 sata HDD do 6TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 285×210×45mm, Težina 1Kg	219,60	183,00
	5006			
<u>DS-7216HQHI-K2</u>		16-KANALNI TURBO HD TRIBRID (ANALOG + HDTVI + AHD + IP) -Rezolucija snimanja HDTVI: 4Mpx lite @15fps, 1080p lite /720p/4CIF@25fps, 3 MP/1080p/720p@15fps, 1080p/720p@15fps, 720p/WD1/4CIF@25fps -Rezolucija snimanja 8 IP kamere: do 6 megapiksela rezolucije -Kompresija: H.265 Pro+/H.265 Pro/H.265+/H.265/H.264+/H.264 -Video/audio ulazi: 16ch BNC, 1ch audio -Video/audio izlazi: CVBS; HDMI 4K (3840X2160/30Hz), 2K (2560x1440/60Hz)... ; VGA 1920 × 1080/60Hz... , 1-ch audio, RCA (2.0 Vp-p, 1 kΩ) -Dodatni ulazi: RJ45 mrežni ulaz, RS-485, 1 USB 2.0 1 USB 3.0 interfejs, -Mrežni protokoli: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF -Hard disk prostor: 2 sata HDD do 10TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 30W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 380×320×48mm, Težina 2Kg	306,00	255,00
	4814			
<u>DS-7216HQHI-K2/A</u>		16-KANALNI TURBO HD TRIBRID (ANALOG + HDTVI + AHD + IP) -Rezolucija snimanja HDTVI: 4Mpx lite @15fps, 1080p lite /720p/4CIF@25fps, 3 MP/1080p/720p@15fps, 1080p/720p@15fps, 720p/WD1/4CIF@25fps -Rezolucija snimanja 8 IP kamere: do 6 megapiksela rezolucije -Kompresija: H.265 Pro+/H.265 Pro/H.265+/H.265/H.264+/H.264 -Video/audio ulazi: 16ch BNC, 4ch audio -Video/audio izlazi: CVBS; HDMI 4K (3840X2160/30Hz), 2K (2560x1440/60Hz)... ; VGA 1920 × 1080/60Hz... , 1-ch audio, RCA (2.0 Vp-p, 1 kΩ) -Dodatni ulazi: RJ45 mrežni ulaz, RS-485, 1 USB 2.0 1 USB 3.0 interfejs, alarmni ulazi/izlazi 16/4 -Mrežni protokoli: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF -Hard disk prostor: 2 sata HDD do 10TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 30W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 380×320×48mm, Težina 2Kg	310,80	259,00
	4882			

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena (racun bez PDV)
DS-7216HUHI-K2  	5354	16-KANALNI TURBO HD HIBRID (ANALOG + AHD + HDTVI + IP) -Rezolucija snimanja: 8fps@8MP, 12fps@5MP, 15fps@4MP; 18fps@3MP, 25fps@1080p, 720p... -Rezolucija snimanja 16 IP kamere: do 8 megapiksela rezolucije -Video/audio ulazi: H.265 Pro+ do H.264 video kompresija, 16ch BNC, 4ch audio -Video/audio izlazi: HDMI/VGA/CVBS (4K 3840X2160/30Hz, 2K 2560x1440/60Hz, 1920x1080/60Hz), 1-ch audio -Dodatni ulazi: RJ45 mrežni ulaz, Alarmni ulazi / izlazi 16/4, RS-485, 1 USB 2.0 interfejs, 1 USB 3.0 -Mrežni protokoli: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF -Hard disk prostor: 2 sata HDD do 10TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 25W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 380×320×48mm, Težina 2Kg	525,60	438,00

HDTVI - HIBRIDNI TURBO HD DVR


TURBO HD

HIKVISION

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (gotovinski)	Cena -20%
DS-7608HUHI-F2/N  TURBO HD 3.0 3 Mpx	4576	8-KANALNI TURBO HD HIBRIDNI (ANALOG + AHD + HDTVI + IP) 8 analognih + 8 IP kamera (do 8Mpx rezolucije) -Rezolucija snimanja: 15fps@2048x1536, 25fps@1920x1080; 720P/WD1/4CIF -Video/audio ulazi: H.264+/H.264 video kompresija, 8ch BNC, 4ch audio -Video/audio izlazi: HDMI/VGA/CVBS (4K 3840X2160/30Hz, 2K 2560x1440/60Hz, 1920x1080/60Hz), 4-ch audio -Dodatni ulazi: RJ45 mrežni ulaz, Alarmni ulazi / izlazi 8/4, RS-485, 1 USB 2.0 interfejs, 1 USB 3.0 -Mrežni protokoli: TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS -Mrežni potok: 128Mbps -Hard disk prostor: 2 sata HDD do 6TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 20W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 380×320×48mm, Težina 2Kg	250,80	209,00
DS-7616HUHI-F2/N  TURBO HD 3.0 3 Mpx	4603	16-KANALNI TURBO HD HIBRIDNI (ANALOG + AHD + HDTVI + IP) 16 analognih + 16 IP kamera (do 8Mpx rezolucije) -Rezolucija snimanja: 15fps@2048x1536, 25fps@1920x1080; 720P/WD1/4CIF -Video/audio ulazi: H.264+/H.264 video kompresija, 16ch BNC, 4ch audio -Video/audio izlazi: HDMI/VGA/CVBS (4K 3840X2160/30Hz, 2K 2560x1440/60Hz, 1920x1080/60Hz), 4-ch audio -Dodatni ulazi: RJ45 mrežni ulaz, Alarmni ulazi / izlazi 16/4, RS-485, 1 USB 2.0 interfejs, 1 USB 3.0 -Mrežni protokoli: TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS -Mrežni potok: 144Mbps -Hard disk prostor: 2 sata HDD do 6TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 40W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 380×320×48mm, Težina 2Kg	460,80	384,00

Nova tehnologija u Hikvision HDTVI sistemima video nadzora. PoC kamere se povezuju sa PoC snimačima kablovima RG59, RG6 ili UTP gde se pored prenosa video signala takođe dobija i napajanje. Maksimalne daljine povezivanja kamera sa snimcima su: 200m za RG59 i RG6, 100m za UTP kabl.

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
<u>DS-7204HQHI-K1/P</u>		4-KANALNI PoC TURBO HD TRIBRID (ANALOG + HDTVI + IP + AHD) -Rezolucija snimanja: Prvi kanal do 3Mpx , 12fps@1920x1080, 25fps@1280x720; ostali kanali -Rezolucija snimanja 1 IP kamere: do 4 megapiskela -Video/audio ulazi: H.265+/ H.265/ H.264+/ H.264 video kompresija, 4ch BNC, 1ch audio -Video/audio izlazi: CVBS, HDMI/VGA (1920X1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz), 1-ch audio, RCA (2.0 Vp-p, 1 kΩ) -Dodatni ulazi: RJ45 mrežni ulaz, RS-485, 2 x USB 2.0 interfejs, -Mrežni protokoli: TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS -Hard disk prostor: 1 sata HDD do 6TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 40W bez HDD, Rad.temp. -10 °C ~+55 °C, Dimenzije 315 × 242 × 45mm, Težina 1,2Kg	144,00	120,00
	5150			
<u>DS-7208HQHI-K2/P</u>		8-KANALNI PoC TURBO HD TRIBRID (ANALOG + HDTVI + AHD + IP) -Rezolucija snimanja: Prvi i drugi kanal do 3Mpx , od trećeg do osmog kanala 12,5fps@1920x1080, 25fps@1280x720; WD1 /4CIF -Rezolucija snimanja 2 IP kamere: do 4 megapiskela -Video/audio ulazi: H.265+/ H.265/ H.264+ / H.264 video kompresija, 8ch BNC, 1ch audio -Video/audio izlazi: CVBS, HDMI/VGA (1920X1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz), 1-ch audio, RCA (1 kΩ) -Dodatni ulazi: RJ45 mrežni ulaz, RS-485, 2 xUSB 2.0 interfejs, -Mrežni protokoli: TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS -Hard disk prostor: 2 sata HDD do 6TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 60W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 315×242×45mm, Težina 1,8Kg	250,80	209,00
	4930			
<u>DS-7216HQHI-K2/P</u>		16-KANALNI PoC TURBO HD TRIBRID (ANALOG + HDTVI + AHD + IP) -Rezolucija snimanja HDTVI: prva četiri kanala do 3Mpx , ostali kanali u 2Mpx 12.5fps -Rezolucija snimanja 2 IP kamere: do 4 megapiksela -Kompresija: H.265+/H.265/H.264+/H.264 -Video/audio ulazi: 16ch BNC, 1ch audio -Video/audio izlazi: CVBS HDMI/VGA 4K (3840X2160/30Hz, 2560x1440/60Hz, 1920x1080/60Hz), 1-ch audio, RCA (2.0 Vp-p, 1 kΩ) -Dodatni ulazi: RJ45 mrežni ulaz, RS-485, 1 USB 2.0 1 USB 3.0 interfejs, -Mrežni protokoli: TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS -Hard disk prostor: 2 sata HDD do 6TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 120W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 380×320×48mm, Težina 2Kg	394,80	329,00
	4931			

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
<u>DS-7604NI-K1</u>		4-KANALNI MREŽNI SNIMAČ -Rezolucija snimanja: 8MP / 6MP / 5MP / 3MP/ 1080P/UXGA/720P/VGA/ 4CIF/ DCIF/ 2CIF/CIF/QCIF -Kompresija: H.265/H.264+/H264 -Ulazno / izlazni saobraćaj: 40/80Mbps -Video/audio izlazi: HDMI/VGA: 4K (3840X2160/30Hz, 1920X1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz), 1-ch audio, RCA (2.0 Vp-p, 1 kΩ) -Dekodiranje: 4-ch@1080 -Dodatni ulazi: RJ45 mrežni ulaz, 1 USB 2.0 interfejs,1 USB 2.0 -Hard disk prostor: 1 sata HDD do 6TB kapaciteta -Opšte: Napajanje 48V DC, Potrošnja 10W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 315×240×45mm, Težina 1Kg	130,80	109,00
	4816			
<u>DS-7604NI-K1/4P</u>		-Rezolucija snimanja: 8MP /6MP /5MP /4MP /3MP /1080P/UXGA/720P/VGA/ 4CIF/ DCIF/ 2CIF/CIF/QCIF -Kompresija: H.265 / H264 / H.264+/ -Ulazno / izlazni saobraćaj: 40/80Mbps -Video/audio izlazi: HDMI/VGA: 4K (3840X2160/30Hz, 1920X1080/60Hz, 1600x1200/60Hz,1280x1024/60Hz, 1280x720/60Hz) 1-ch audio, RCA (2.0 Vp-p, 1 kΩ), -Dekodiranje: 4-ch @ 1080p -POE interfejs: 4xRJ-45 100Mb/s, full-duplex ethernet interface, ≤40W -Dodatni ulazi: RJ45 mrežni ulaz, 1 USB 2.0 interfejs prednji,1 USB 2.0 zadnji -Hard disk prostor: 1 sata HDD do 6TB kapaciteta -Opšte: Napajanje 48V DC, Potrošnja 10W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 315×240×48mm, Težina 1Kg	187,20	156,00
	4580			
<u>DS-7608NI-K2</u>		8-KANALNI MREŽNI SNIMAČ -Rezolucija snimanja: 8MP/ 6MP / 5MP / 3MP/ 1080P/UXGA/720P/VGA/ 4CIF/ DCIF/ 2CIF/CIF/QCIF -Kompresija: H.265/H.264+/H264 -Ulazno / izlazni saobraćaj: 80/160Mbps -Video/audio izlazi: HDMI/VGA 4K (3840X2160/30Hz,1920X1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz), 1-ch audio, RCA (2.0 Vp-p, 1 kΩ) -Dekodiranje: 2-ch @ 4K, or 8-ch @ 1080p -Dodatni ulazi: RJ45 mrežni ulaz, Alarmni ulazi / izlazi 4/1, RS-485,1 USB 2.0 interfejs,1 USB 3.0 -Hard disk prostor: 1 sata HDD do 6TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 385×315×52mm, Težina 1Kg	190,80	159,00
	4817			
<u>DS-7608NI-K2/8P</u>		8-KANALNI MREŽNI SNIMAČ -Rezolucija snimanja: 8MP /6MP /5MP /4MP /3MP /1080P/UXGA/720P/VGA/ 4CIF/ DCIF/ 2CIF/CIF/QCIF -Kompresija: H.265 / H264 / H.264+ / MPEG4 -Ulazno / izlazni saobraćaj: 80/160Mbps -Video/audio izlazi: HDMI/VGA: 4K (3840X2160/30Hz, 2K 2560X1440/60HZ, 1920X1080/60Hz, 1600x1200/60Hz,1280x1024/60Hz, 1280x720/60Hz, 1024X768/60Hz) 1-ch audio, RCA (2.0 Vp-p, 1 kΩ), -Dekodiranje: 2-ch @ 4K ili 8-ch @ 1080p -POE interfejs: 8xRJ-45 100Mb/s, full-duplex ethernet interface, ≤120W -Dodatni ulazi: RJ45 mrežni ulaz, 1 USB 2.0 interfejs prednji,1 USB 3.0 zadnji, Alarm in/out 4/1 -Hard disk prostor: 1 sata HDD do 6TB kapaciteta -Opšte: Napajanje 100-240 VAC, Potrošnja 15W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 385×315×52mm, Težina 3Kg	300,00	250,00
	5005			

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
DS-7608NI-I2  	4129	8-KANALNI MREŽNI SNIMAČ -Rezolucija snimanja: 12MP / 8MP / 6MP / 5MP / 3MP/ 1080P/UXGA/720P/VGA/ 4CIF/ DCIF/ 2CIF/CIF/QCIF, -Ulazno / izlazni saobraćaj: 80/256Mbps -Kompresija: H.265+ / H.265 / H264 / H.264+ / MPEG4 -Video/audio izlazi: HDMI/VGA/ 4K (3840X2160/60Hz, 3840X2160/30Hz, 1920X1080P/60Hz), 1-ch audio, -Dodatni ulazi: 1 RJ45 mrežni ulaz, RS-232, Alarmni ulazi/izlazi 4/1, 1X USB 2.0 interfejs, 1X USB 3.0 -Hard disk prostor: 2 sata HDD do 8TB kapaciteta -Opšte: Napajanje 100 ~ 240 VAC, 6.3 A, 50 ~ 60 Hz, Potrošnja 40W, Radna temperatura -10 °C ~+55 °C, Dimenzije 385×315×52mm, Težina 3Kg	265,20	221,00
DS-7616NI-K2 	4815	16-KANALNI MREŽNI SNIMAČ -Rezolucija snimanja: 8MP/ 6MP / 5MP / 3MP/ 1080P/UXGA/720P/VGA/ 4CIF/ DCIF/ 2CIF/CIF/QCIF -Kompresija: H.265/H.264+/H264 -Ulazno / izlazni saobraćaj: 160/160Mbps -Video/audio izlazi: HDMI/VGA 4K (3840X2160/30Hz, 1920X1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz), 1-ch audio, RCA (2.0 Vp-p, 1 kΩ) -Dekodiranje: 2-ch @ 4K, or 8-ch @ 1080p -Dodatni ulazi: RJ45 mrežni ulaz, Alarmni ulazi / izlazi 4/1, RS-485, 1 USB 2.0 interfejs, 1 USB 3.0 -Hard disk prostor: 2 sata HDD do 6TB kapaciteta -Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 385×315×52mm, Težina 1Kg	222,00	185,00
DS-7616NI-K2/16P 	5132	16-KANALNI MREŽNI SNIMAČ -Rezolucija snimanja: 8MP /6MP /5MP /4MP /3MP /1080P/UXGA/720P/VGA/ 4CIF/ DCIF/ 2CIF/CIF/QCIF -Kompresija: H.265 / H264 / H.264+ / MPEG4 -Ulazno / izlazni saobraćaj: 160/160Mbps -Video/audio izlazi: HDMI/VGA: 4K (3840X2160/30Hz, 2K 2560X1440/60HZ, 1920X1080/60Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024X768/60Hz) 1-ch audio, RCA (2.0 Vp-p, 1 kΩ), -Dekodiranje: 2-ch @ 4K ili 8-ch @ 1080p -POE interfejs: 16xRJ-45 100Mb/s, full-duplex ethernet interface, ≤200W -Dodatni ulazi: RJ45 mrežni ulaz, 1 USB 2.0 interfejs prednji, 1 USB 3.0 zadnji, Alarm in/out 4/1 -Hard disk prostor: 2 sata HDD do 6TB kapaciteta -Opšte: Napajanje 100-240 VAC, Potrošnja 15W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 385×315×52mm, Težina 3Kg	399,60	333,00
DS-7632NI-I2  	4611	32-KANALNI MREŽNI SNIMAČ -Rezolucija snimanja: 12MP / 8MP / 6MP / 5MP / 3MP/ 1080P/UXGA/720P/VGA/ 4CIF/ DCIF/ 2CIF/CIF/QCIF, H.264 / H.265 -Ulazno / izlazni saobraćaj: 256/256Mbps -Video/audio izlazi: HDMI/VGA/ (3840X2160/60Hz, 3840X2160/30Hz, 1920X1080P/60Hz), 1-ch audio, -Dodatni ulazi: 2 x RJ45 mrežni ulaz, RS-485, RS-232, Alarmni ulazi/izlazi 4/1, 2X USB 2.0 interfejs, 1X USB 3.0 -Hard disk prostor: 2 sata HDD do 8TB kapaciteta -Opšte: Napajanje 100 ~ 240 VAC, 6.3 A, 50 ~ 60 Hz, Potrošnja 20W, Radna temperatura -10 °C ~+55 °C, Dimenzije 445×390×70mm, Težina 5Kg	477,60	398,00

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
DS-9632NI-I8  	4262	32-KANALNI MREŽNI SNIMAC -Rezolucija snimanja: 12MP / 8MP / 6MP / 5MP / 3MP/ 1080P/UXGA/720P/VGA/ 4CIF/ DCIF/ 2CIF/CIF/QCIF, H.264 / H.265 -Ulazno / izlazni saobraćaj: 320/256Mbps, ili 200/200Mbps kada je RAID uključen -Video/audio izlazi: HDMI 1/VGA 1/ (3840X2160/60Hz, 3840X2160/30Hz, 1920X1080P/60Hz), HDMI 2/VGA2 (1920x1080/60Hz, 1280x1024Hz, 1280x720/60Hz), 2-ch RCA -Dodatni ulazi: 2 x RJ45 mrežni ulaz, RS-485, RS-232, Alarmni ulazi/izlazi 16/4, 2X USB 2.0 interfejs, 1X USB 3.0 -Hard disk prostor: 8 sata HDD do 6TB kapaciteta, Disk Array RAID0, RAID1, RAID5, RAID10 -Opšte: Napajanje 100 ~ 240 VAC, 50 ~ 60 Hz, Potrošnja 30W, Radna temperatura -10 °C ~+55 °C, Dimenzije 445x470x90mm, Težina 10Kg	1.490,40	1.242,00

HIKVISION MONITORI

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
LED Monitor DS-D5019QE-B 19" 	5255	LED Backlight monitor Dijagonala: 18,5" Rezolucija: 1366x768 Osvetljenje: 200cd/m2 Kontrast: 600:1 Odziv: 5ms Ugao gledanja: H 90°, V 65° Boje: 16.7M Ulazi: HDMI, VGA VESA mount: 75x75 3D Comb filter, 3D De-Interlace, 3D Noise Reduction Dimenzije: 445.58mmx274.99mm*x4.6mm	122,40	102,00
LED Monitor DS-D5022QE-B 22" 	5256	LED Backlight monitor Dijagonala: 22" Rezolucija: 1920x1080 Osvetljenje: 250cd/m2 Kontrast: 1000:1 Odziv: 5ms Ugao gledanja: H 170°, V 160° Boje: 16.7M Ulazi: HDMI, VGA VESA mount: 100x100 3D Comb filter, 3D De-Interlace, 3D Noise Reduction Dimenzije: 511mmx377mmx170mm	151,20	126,00

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
DS-3E0105P-E				
	4818	4 x 10/100 Mbps Auto MDX PoE 1 x 10/100/1000 Mbps 4kV zaštita od prenapona PoE buđžet 58W Dimenzije: 132 x 93.3 x 27.6mm	69,60	58,00
DS-3E0109P-E				
	4819	8 x 10/100 Mbps Auto MDX PoE 1 x 10/100/1000 Mbps 4kV zaštita od prenapona PoE buđžet 123W Podržava 802.3 AF/AT standarde do 30W snage po portu Dimenzije: 235 x 103 x 27mm	190,80	159,00
DS-3E0318P-E				
	4820	16 x 10/100 Mbps Auto MDX PoE 2 x 1000 Mbps Combo port 4kV zaštita od prenapona PoE buđžet 230W Podržava 802.3 AF/AT standarde do 30W snage po portu Dimenzije: 440 x 285 x 43mm	423,60	353,00

MOBILNI SNIMAČI

DS-M5504HMI/GW

	4047	4-KANALNI MOBILNI SNIMAČ - Rezolucija snimanja: ch1-4: 25fps@WD1/4CIF/2CIF/CIF - Video/audio ulazi: H.264 video kompresija, 4ch, 4ch audio avioniks - Video/audio izlazi: 1xVGA, 1ch CVBS avioniks, 1ch audio avioniks (600Ω) - Hard disk prostor: 1 x 2,5" HDD do 1TB kapaciteta u antišok fioci - Dodatni interfejsi: 1x USB 2.0, RS-232, RS-485 - Alarmni interfejs: ulazi / izlazi: 7(visok/nizak nivo) +1 (pulsni) / 2 (relejni 5V) , IC daljinski - Konekcije: 1xRJ45, 1 x SMA 3G antena, 1 x GPS antena - Slotovi: 1x SIM, 1x SD/SDHC(do 32GB) - Opšte: Napajanje do +6 do +36V DC potrošnje do max 20W, pripravnost 0,5W, Napajanje kamera iz DVR: +12V DC/2A, +5V DC/ 1A avioniks konektori Radna temperatura -15 °C ~+55 °C, Dimenzije 1 DIN (180 ×153×50 mm), Težina do 2,5Kg Napomena: Uređaj podržava MVA(lokalno) i iVMS-5200p platformski software	793,50	661,25
---	------	---	--------	--------

DS-2CS58A1P-IRS

	4088	Antivandal dome kamera - Čip: Kolor 1/3" DIS 700TV linija, - Osetljivost: 0.1 Lux @(F1.2, AGC ON), - IC osvetljenje: 10 IR dioda dometa do 20 metara, IR cut filter - Opšte: Napajanje 12V DC, Potrošnja 4W Radna temperatura -40 °C ~+60 °C, IP 66 Dimenzije 97 × 46,6 × 99,5mm Težina 300g	kontakt	
---	------	--	---------	--





NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
HIKVISION HARD DISC <u>WD10PURX-78 PURPLE</u> <u>1TB</u> 	3861	Western Digital, 1TB Purple, IntelliPower, SATA III, 64MB	80,40	67,00
HIKVISION HARD DISC <u>WD20PURX-78 PURPLE</u> <u>2TB</u> 	4091	Western Digital, 2TB Purple, IntelliPower, SATA III, 64MB	111,60	93,00
HIKVISION HARD DISC <u>WD30PURX-78 PURPLE</u> <u>3TB</u> 	3523	Western Digital, 3TB Purple, IntelliPower, SATA III, 64MB	168,00	140,00
HIKVISION HARD DISC <u>WD40PURX-78 PURPLE</u> <u>4TB</u> 	4195	Western Digital, 4TB Purple, IntelliPower, SATA III, 64MB	196,80	164,00
HIKVISION HARD DISC <u>WD60PURX-78 PURPLE</u> <u>6TB</u> 	3844	Western Digital, 6TB Purple, IntelliPower, SATA III, 64MB	331,20	276,00

TOSHIBA HDD



HARD DISC TOSHIBA 2TB <u>DT01ABA200V</u> 	4792	Toshiba 2TB , IntelliPower, SATA III, 64MB	108,00	90,00
HARD DISC TOSHIBA 3TB <u>DT01ABA300V</u> 	4793	Toshiba 3TB , IntelliPower, SATA III, 64MB	156,00	130,00

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
DOME DS-2CE56D8T-ITME 2,8mm	5143	Antivandal PoC dome kamera -Čip: Kolor CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) rezolucije,2,8mm optika -OSD meni: 3D DNR , DPC , ATW, WDR 120dB -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.005 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: Smart IR diode dometa do 20 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 3,6W Radna temperatura -40 °C ~+60 °C, IP 67 Dimenzije 91 × 82,6 × 68,3 mm, Težina 350g	55,20	46,00
 				
IR BULLET DS-2CE16D8T-IT3E 3,6mm	5140	Bullet PoC kamera -Čip: Kolor CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) rezolucije,3,6mm optika -OSD meni: 3D DNR , DPC , ATW, WDR 120dB -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.005 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: EXIR Smart dioda dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4W Radna temperatura -30 °C ~+60 °C, IP 67 Dimenzije 86×82,8×220mm, Težina 680g	66,00	55,00
  				
DOME DS-2CC52D9T-AVPIT3ZE 2.8-12mm	5141	2MP Ultra Low-Light PoC Dome Camera 2.0 Megapixel progressive scan CMOS Analog HD output, up to 1080P resolution 2.8-12mm motorized vari-focal lens Auto focus OSD menu 120dB true WDR EXIR 2.0, up to 40m IR distance IP67, IK10 Up the Coax(HIKVISION-C) PoC 1 alarm in/out	156,00	130,00
				



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
DOME DS-2CE56C0T-IRMF 2,8mm  	4801	Antivandal dome kamera -Čip:CMOS 1 Megapiksel HD 720P (1280x720) rezolucije,2,8mm optika -Efektivni pikseli: 1296(H)*732(V) -Osetljivost: 0.1 Lux @(F1.2,AGC ON), 0 Lux with IR -Signalni prekidač: HDTVI,CVI,AHD,CVBS -IC osvetljenje: 24 Smart IR dioda dometa do 20 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4W Radna temperatura -40 °C ~+60 °C, IP 66 Dimenzije 89.6 × 59.1 mm, Težina 340g	25,20	21,00
DOME DS-2CE56D0T-IRMF 2,8mm  	4761	Antivandal dome kamera -Čip: Kolor 1/3" CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) rezolucije, 2,8mm optika -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -Signalni prekidač: HDTVI,CVI,AHD,CVBS -IC osvetljenje: 24 Smart IR dioda dometa do 20 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 3,5W Radna temperatura -40 °C ~+60 °C, IP 66 Dimenzije 89.6 × 59.1 mm, Težina 400g	34,80	29,00
DOME DS-2CE56D0T-IRMF 3,6mm  	4905	Antivandal dome kamera -Čip: Kolor 1/3" CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) rezolucije,3,6mm optika -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -Signalni prekidač: HDTVI,CVI,AHD,CVBS -IC osvetljenje: 24 Smart IR dioda dometa do 20 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 3,5W Radna temperatura -40 °C ~+60 °C, IP 66 Dimenzije 89.6 × 59.1 mm, Težina 400g	34,80	29,00
DOME DS-2CE56D7T-ITM 2,8mm  	4837	Antivandal dome kamera -Čip: Kolor 1/3" CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) rezolucije,2,8mm optika -OSD meni: 3D DNR , DPC , ATW, WDR 120dB -Efektivni pikseli: 1930(H)*1088(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: Smart IR diode dometa do 20 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 3,5W Radna temperatura -40 °C ~+60 °C, IP 66 Dimenzije 89.6 × 59.1 mm, Težina 400g	51,60	43,00
DOME DS-2CE71D8T-PIRL 2,8mm    	5230	Dome kamera -Čip: 2 megapixels progressive scan CMOS, -Rezolucija snimanja: 1920(H)*1080(V), -Osetljivost: 0.005 Lux @(F1.2,AGC ON), 0 Lux with IR, -OSD meni: 3D DNR , DPC ,ATW, WDR 120dB, -IC osvetljenje: Smart dioda dometa do 20 metara, IR cut filter, -PIR detekcija: Ugao 110°, daljina 11m, -Opšte: Napajanje 12V DC, Potrošnja 4,5W, Radna temperatura -40 °C ~+60 °C, IP 67, Dimenzije 109,8×89,75, Težina 310g	57,60	48,00
DOME DS-2CE56D0T-IT3F 2,8mm  	4878	Dome kamera -Čip:Kolor 1/3" CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) rezolucije,2,8mm optika -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -Signalni prekidač: HDTVI,CVI,AHD,CVBS -IC osvetljenje: EXIR Smart diode dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 3,5W Radna temperatura -20 °C ~+45 °C, IP 66 Dimenzije 110 × 93.2 mm, Težina 350g	42,00	35,00



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
DOME DS-2CE56D0T-IT3 2,8mm 	4221	Dome kamera -Čip:Kolor 1/3" CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) rezolucije,2,8mm optika -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: EXIR Smart diode dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 3,5W Radna temperatura -20 °C ~+45 °C, IP 66 Dimenzije 110 × 93.2 mm, Težina 350g	39,60	33,00
DOME DS-2CE56D0T-IT3F 3,6mm  	4881	Dome kamera -Čip:Kolor 1/3" CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) rezolucije, 3,6mm optika -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -Signalni prekidač: HDTVI,CVI,AHD,CVBS -IC osvetljenje: EXIR Smart diode dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 3,5W Radna temperatura -20 °C ~+45 °C, IP 66 Dimenzije 110 × 93.2 mm, Težina 350g	42,00	35,00
DOME DS-2CE56D0T-IT3 3,6mm 	4222	Dome kamera -Čip:Kolor 1/3" CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) rezolucije, 3,6mm optika -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: EXIR Smart diode dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 3,5W Radna temperatura -20 °C ~+45 °C, IP 66 Dimenzije 110 × 93.2 mm, Težina 350g	39,60	33,00
DOME DS-2CE56D7T-IT3 2,8mm  	4803	Dome kamera -Čip:CMOS 2 Megapiksela FULL HD 1080P (1920x1080) rezolucije -Efektivni pikseli: 1928(H)*1088(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -OSD meni:AGC, D/N, ATW, BLC, WDR 120dB -IC osvetljenje: EXIR Smart diode dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 3,5W Radna temperatura -40 °C ~+45 °C, IP 66 Dimenzije 110 × 93.2 mm, Težina 350g	60,00	50,00
DOME DS-2CE56D0T-VFIR3F  	4840	Antivandal Dome kamera -Čip:Kolor 1/2,7" CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) -Optika: varifokal 2,8-12mm -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), -Signalni prekidač: HDTVI,CVI,AHD,CVBS -IC osvetljenje: 24 Smart dioda dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4,5W Radna temperatura -40 °C ~+60 °C, IP66, Dimenzije 130,54 × 102.4 mm, Težina 710g	67,20	56,00
DOME DS-2CE56D8T-IT3Z   	5221	Antivandal Dome kamera -Čip: 2 megapixels, progressive scan CMOS, -Optika: motorizovani varifokal 2,8-12mm -Rezolucija snimanja: 1920(H)*1080(V), -Osetljivost: 0.005 Lux @(F1.8,AGC ON), -OSD meni: 3D DNR , DPC ,ATW, WDR 120dB , -IC osvetljenje: Smart diode dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 8 W, Radna temperatura -40 °C ~+60 °C, IP67, Dimenzije 134 × 123,9 x 111,4 mm, Težina 750g	100,80	84,00



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
DOME DS-2CE56F7T-ITM 2,8mm 	4367	Antivandal dome kamera -Čip:CMOS 3 Megapiksela (2048x1536) rezolucije,2,8mm optika -OSD meni: 3D DNR , DPC ,ATW, WDR 120dB -Efektivni pikseli: 2052(H)*1536(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: EXIR Smart dioda dometa do 20 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 5W Radna temperatura -30 °C ~+60 °C, IP 66 Dimenzije 91 x 82.6 x 68,3 mm, Težina 350g	52,80	44,00
DOME DS-2CE56H0T-ITMF 2.8mm 	5319	Antivandal dome kamera -Čip:CMOS 5 Megapiksela (2560x1944) rezolucije,2,8mm optika -OSD meni: AGC, D/N mode, BLC, DWDR -Signalni prekidač: HDTVI,CVI,AHD,CVBS -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: Smart diode dometa do 20 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4,3W Radna temperatura -40 °C ~+60 °C, IP 67 Dimenzije 91 x 82.6 x 68,3 mm, Težina 350g	51,60	43,00
DOME DS-2CE56H0T-IT3F 2.8mm 	5320	Dome kamera -Čip:CMOS 5 Megapiksela (2560x1944) rezolucije,2,8mm optika -OSD meni: AGC, D/N mode, BLC, DWDR -Signalni prekidač: HDTVI,CVI,AHD,CVBS -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: Smart diode dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4,3W Radna temperatura -40 °C ~+60 °C, IP 67 Dimenzije 110 x 93.2, Težina 350g	58,80	49,00



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
DOME DS-2CE56H0T-IT3F 3.6mm   	5321	Dome kamera -Čip:CMOS 5 Megapiksela (2560x1944) rezolucije ,3,6mm optika -OSD meni: AGC, D/N mode, BLC, DWDR -Signalni prekidač: HDTVI,CVI,AHD,CVBS -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: Smart diode dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4,3W Radna temperatura -40 °C ~+60 °C, IP 67 Dimenzije 110 x 93.2, Težina 350g	58,80	49,00
DOME DS-2CE56H0T-IT3ZF   	5326	Dome kamera -Čip:CMOS 5 Megapiksela (2592x1944) rezolucije -Optika: varifokal motorizovan 2,7-13,5mm -OSD meni: AGC, D/N mode, BLC, DWDR -Signalni prekidač: HDTVI,CVI,AHD,CVBS -Efektivni pikseli: 2592(H)*1944(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: EXIR Smart dioda dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 6,3W Radna temperatura -40 °C ~+60 °C, IP 67 Dimenzije 123,86 x 134,3 x 110,11 mm, Težina 580g	96,00	80,00
DOME DS-2CE56H1T-ITZ  	5071	Unutrašnja Dome kamera -Čip:CMOS 5 Megapiksela (2592x1944) rezolucije -Optika: varifokal motorizovan 2,8-12mm -OSD meni: 3D DNR , DPC ,ATW, -Efektivni pikseli: 2592(H)*1944(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: EXIR Smart dioda dometa do 30 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4,5W Radna temperatura -40 °C ~+60 °C, IP 65 Dimenzije 136x102 mm, Težina 600g	100,80	84,00
DOME DS-2CE56H1T-VPIT3Z  	5128	Dome kamera -Čip:CMOS 5 Megapiksela (2592x1944) rezolucije -Optika: varifokal motorizovan 2,8-12mm -OSD meni: 3D DNR , DPC ,ATW, -Efektivni pikseli: 2592(H)*1944(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: EXIR Smart dioda dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4,5W Radna temperatura -40 °C ~+60 °C, IP 67 Dimenzije 145,2x124,1 mm, Težina 600g	108,00	90,00



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
SPEED DOME DS-2AE5123T-A	3624	Motorizovana upravljiva kupolna kamera. -Čip:Kolor 1/3" CMOS, 1,3 Megapiksela HD 720P (1280x720) rezolucije, -Optika: 23x optički zum, 16x digitalni zum -OSD meni: 3D DNR , DPC ,ATW, BLC, DWDR -Efektivni pikseli: 1280(H)*720(V) -Osetljivost: 0.02 Lux @(F1.2,AGC ON), -PTZ: 256 preset pozicija, 8 patrol moda, rotacija 360° -Opšte: Napajanje 24V AC, Potrošnja 12W, Zaštita od udara groma Radna temperatura -30 °C ~+60 °C, IP66, Težina 3Kg	459,60	383,00
SPEED DOME DS-2AE7123TI-A	4196	Motorizovana upravljiva kupolna kamera. -Čip:Kolor 1/3" CMOS, 1,3 Megapiksela HD 720P (1280x720) -Optika: 23x optički zum, 16x digitalni zum -OSD meni: 3D DNR , DPC ,ATW, BLC, DWDR -Efektivni pikseli: 1280(H)*720(V) -Osetljivost: 0.02 Lux @(F1.2,AGC ON), -PTZ: 256 preset pozicija, 8 patrol moda, rotacija 360° -Opšte: Napajanje 24V AC, Potrošnja 30W, Zaštita od udara groma, domet IC dioda 120m Radna temperatura -30 °C ~+60 °C, IP66, Težina 4,5Kg	571,14	475,95
SPEED DOME DS-2AE7232TI-A	5337	Motorizovana upravljiva kupolna kamera. -Čip:Kolor 1/3" CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) -Optika: 32x optički zum, 16x digitalni zum -OSD meni: 3D DNR , DPC ,ATW, BLC, DWDR -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.02 Lux @(F1.2,AGC ON), -PTZ: 256 preset pozicija, 8 patrol moda, rotacija 360° -Opšte: Napajanje 24V AC, Potrošnja 50W, Zaštita od udara groma, domet IC dioda 120m Radna temperatura -30 °C ~+60 °C, IP66, Težina 4,5Kg	744,00	620,00



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
Plafonski nosač				
<u>DS-1663ZJ</u>				
	4601	Plafonski nosač dužine 5,7cm za PTZ kamere HIKVISION	17,16	14,30
Plafonski nosač				
<u>DS-1661ZJ</u>				
	4600	Plafonski nosač dužine 20cm za PTZ kamere HIKVISION	42,90	35,75
Zidni nosač				
<u>DS-1602ZJ</u>				
	3711	Zidni nosač za PTZ kamere HIKVISION	24,00	20,00
Zidni nosač sa adapterom				
<u>DS-1602ZJ CORNER</u>				
	3712	Zidni ugaoni nosač sa adapterom za PTZ kamere HIKVISION	48,30	40,25
DS-1601ZJ - BOX KUĆIŠTE SA NOSAČEM				
<u>DS-1602ZJ</u>				
	3518	Nazidno kućište za PTZ kamere sa nosačem. IP 66 , Dimenzije 310 (V) x 175 (Š) x 90 (D) mm , Težina 2,5 kg	103,20	86,00
DŽOJSTIK ZA PTZ KAMERE				
<u>DS-1005KI</u>				
 	4126	Tastatura za kontrolu PTZ kamera -Podržani sistemi: Windows XP/7/8/8.1/10 -Interfejsi: USB 2.0, DirectX -Kontrola: Džojstik (upravljivost 3 ose, rotacija, zoom) -Tasteri: 15 programibilnih tastera -Napajanje: 5V DC kroz USB -Potrosnja: < 5W -Radna temperatura -10 °C ~ +55 °C	264,00	220,00



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
IR BULLET DS-2CE16C0T-IT3F 3,6mm  	4802	Bullet kamera -Čip:CMOS 1 Megapiksel HD 720P (1280x720) rezolucije 3,6mm optika -Efektivni pikseli: 1296(H)*732(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -Signalni prekidač: HDTVI,CVI,AHD,CVBS -IC osvetljenje: EXIR Smart dioda dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4W Radna temperatura -40 °C ~+60 °C, IP 66 Dimenzije 86×82,8×220mm, Težina 700g	34,80	29,00
IR BULLET DS-2CE16D0T-IRF 2,8mm  	4997	Bullet kamera -Čip:Kolor 1/3" CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) rezolucije,2,8mm optika -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -Signalni prekidač: HDTVI,CVI,AHD,CVBS -IC osvetljenje: 24 Smart dioda dometa do 20 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4W Radna temperatura -30 °C ~+60 °C, IP 66 Dimenzije 70x149,5 mm, Težina 360g	37,20	31,00
IR BULLET DS-2CE16D8T-IT 2.8mm  	5284	Bullet kamera -Čip: 2 megapixels progressive scan CMOS, -Rezolucija snimanja: 1920(H)*1080(V), -Osetljivost: 0.005 Lux @(F1.2,AGC ON), 0 Lux with IR, -OSD meni: 3D DNR , DPC ,ATW, WDR 120dB, -IC osvetljenje: Smart dioda dometa do 20 metara, IR cut filter, -Opšte: Napajanje 12V DC, Potrošnja 4W, Radna temperatura -40 °C ~+60 °C, IP 67, Dimenzije 58 × 61 × 163mm, Težina 350g	48,00	40,00
IR BULLET DS-2CE12D8T-PIRL 3,6mm  	5229	Bullet kamera -Čip: 2 megapixels progressive scan CMOS, -Rezolucija snimanja: 1920(H)*1080(V), -Osetljivost: 0.005 Lux @(F1.2,AGC ON), 0 Lux with IR, -OSD meni: 3D DNR , DPC ,ATW, WDR 120dB, -IC osvetljenje: Smart dioda dometa do 20 metara, IR cut filter, -PIR detekcija: Ugao 110°, daljina 11m, -Opšte: Napajanje 12V DC, Potrošnja 4,5W, Radna temperatura -40 °C ~+60 °C, IP 67, Dimenzije 88,6×81,3×224,7mm, Težina 430g	60,00	50,00
IR BULLET DS-2CE16D0T-IT3F 3,6mm  	4922	Bullet kamera -Čip:Kolor 1/3" CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) rezolucije,3,6mm optika -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -Signalni prekidač: HDTVI,CVI,AHD,CVBS -IC osvetljenje: EXIR Smart dioda dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4W Radna temperatura -30 °C ~+60 °C, IP 66 Dimenzije 86×82,8×220mm, Težina 430g	46,80	39,00
IR BULLET DS-2CE16D0T-IT5F 3,6mm  	4965	Bullet kamera -Čip:Kolor 1/3" CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) rezolucije,3,6mm optika -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -Signalni prekidač: HDTVI,CVI,AHD,CVBS -IC osvetljenje: EXIR Smart dioda dometa do 80 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 6W Radna temperatura -30 °C ~+60 °C, IP 66 Dimenzije 86×82,8×220mm, Težina 430g	54,00	45,00
IR BULLET DS-2CE16D7T-IT3 3,6mm  	4716	Bullet kamera -Čip:Kolor 1/3" CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) rezolucije,3,6mm optika -Efektivni pikseli: 1920(H)*1080(V) -OSD meni:3D DNR , DPC ,ATW, WDR 120dB -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: EXIR Smart dioda dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4W Radna temperatura -30 °C ~+60 °C, IP 66 Dimenzije 86×82,8×220mm, Težina 430g	63,60	53,00



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
IR BULLET DS-2CE16D0T-VFIR3F  	4904	Bullet kamera -Čip:Kolor 1/3" CMOS, 2 Megapiksela FULL HD 1080P (1920x1080) -Optika: varifokal 2,8-12mm -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), -Signalni prekidač: HDTVI,CVI,AHD,CVBS -IC osvetljenje: 42 Smart dioda dometa do 40 metara, -Opšte: Napajanje 12V DC, Potrošnja 6W Radna temperatura -30 °C ~+60 °C, IP66, Dimenzije 92x84,8x269,6mm, Težina 1000g	67,20	56,00
IR BULLET DS-2CE16D8T-IT3Z   EXIR	5220	Bullet kamera -Čip: 2 megapixels, progressive scan CMOS, -Optika: motorizovani varifokal 2,8-12mm, -Rezolucija snimanja: 1920(H)*1080(V), -Osetljivost: 0.005 Lux @(F1.8,AGC ON), -OSD meni: 3D DNR , DPC ,ATW, WDR 120dB , -IC osvetljenje: Smart diode dometa do 40 metara, IR cut filter, -Opšte: Napajanje 12V DC, Potrošnja 8 W, Radna temperatura -40 °C ~+60 °C, IP67, Dimenzije 92 × 89 x 269,6 mm, Težina 900g	102,00	85,00
IR BULLET DS-2CE16F7T-IT3 3,6mm   3 Mpx EXIR	4383	Bullet kamera -Čip:CMOS 3 Megapiksela (2048x1536) rezolucije, 3,6mm optika -OSD meni: 3D DNR , DPC ,ATW, WDR 120dB -Efektivni pikseli: 2052(H)*1536(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: EXIR Smart dioda dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 5W Radna temperatura: -40 °C ~+60 °C, IP 66 Dimenzije 91 x 82.6 x 68,3 mm, Težina 350g	72,00	60,00
IR BULLET DS-2CE16H0T-IT3F 3.6mm   EXIR 5 Mpx	5322	Bullet kamera -Čip:CMOS 5 Megapiksela (2560x1944) rezolucije -OSD meni: AGC, D/N, ATW, BLC, DWDR -Signalni prekidač: HDTVI,CVI,AHD,CVBS -Efektivni pikseli: 2560(H)*1944(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: EXIR Smart dioda dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4,3W Radna temperatura -40 °C ~+60 °C, IP 67 Dimenzije 86,7 x 81.6 x 226 mm, Težina 680g	61,20	51,00
IR BULLET DS-2CE16H0T-IT5F 3.6mm   EXIR 5 Mpx	5323	Bullet kamera -Čip:CMOS 5 Megapiksela (2560x1944) rezolucije -OSD meni: AGC, D/N, ATW, BLC, DWDR -Signalni prekidač: HDTVI,CVI,AHD,CVBS -Efektivni pikseli: 2560(H)*1944(V) -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: EXIR Smart dioda dometa do 80 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4,3W Radna temperatura -40 °C ~+60 °C, IP 67 Dimenzije 86,7 x 81.6 x 226 mm, Težina 680g	68,40	57,00
IR BULLET DS-2CE16H0T-IT3ZF 2.7-13.5mm   EXIR 5 Mpx	5324	Bullet kamera -Čip:CMOS 5 Megapiksela (2560x1944) rezolucije -OSD meni: AGC, D/N, ATW, BLC, DWDR -Optika: varifokal motorizovan 2,7-13,5mm -Signalni prekidač: HDTVI,CVI,AHD,CVBS -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: EXIR Smart dioda dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 6,3W Radna temperatura -40 °C ~+60 °C, IP 67 Dimenzije 84,5 x 92 x 255,1 mm, Težina 665g	103,20	86,00

**PINHOLE KAMERA**
DS-2CS54D8T-PH 3,7mm

5149

Mini kockica

-Čip: 2 megapixels progressive scan CMOS,
 -Rezolucija snimanja: 1920(H)*1080(V), optika 3,7mm,
 -Osetljivost: 0.005 Lux,
 -OSD meni: 3D DNR, BLC, ATW, **WDR 120dB**,
 -Opšte: Napajanje 12V DC, Potrošnja 1,5 W
Radna temperatura -40 °C ~+60 °C
 Dimenzije 32,4 × 32,4 × 22 mm

58,80

49,00

HDTVI - BEAR DOME KAMERE

**DOME**
B-100 3,6mm

4245

Dome kamera

-Čip: Kolor CMOS
1 Megapiksel HD720P 3,6mm optika
 -Osetljivost: 0.01 Lux @(F1.2, AGC ON), 0 Lux with IR
 -IC osvetljenje: Jedna Smart EXIR dioda dometa do 20 metara, IR cut filter
 -Opšte: Napajanje 12V DC, Potrošnja 4W
Radna temperatura -40 °C ~+60 °C, IP66 Dimenzije 130,54 × 93.54 mm, Težina 380g

20,40

17,00

VANDALPROOF IR DOME
B-109C 3,6mm

4701

Antivandal dome kamera

-Čip: Kolor 1/2,9" SONY CMOS,
2,1 Megapiksela 1080P (1920x1080) 3,6mm optika
 -Signalni prekidač: **HDTVI, CVI, AHD, CVBS**
 -OSD meni: DWDR, 3DNR, UTC, OSD
 -Osetljivost: 0.01 Lux @(F1.2, AGC ON), 0 Lux with IR
 -IC osvetljenje: 18 IR dioda dometa do 20 metara, IR cut filter
 -Opšte: Napajanje 12V DC, Potrošnja 500mA
 Radna temperatura -10 °C ~+50 °C, Dimenzije 94×76 mm,
 Težina 450g

33,60

28,00



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
IR BULLET B-250S 	3871	Bullet kamera -Čip: Kolor 1/2,9" SONY CMOS 2,1 Megapiksela 1080P (1920x1080) rezolucije, -Signalni prekidač: HDTVI,CVI,AHD,CVBS -Optika: varifokal 2,8-12mm -OSD meni: WDR, 3DNR, UTC, OSD -Osetljivost: 0.01 Lux @(F1.2,AGC ON), -IC osvetljenje: 4 diode dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 1000mA Radna temperatura -10 °C ~+50 °C, IP 66, Dimenzije 211 × 92× 90 mm, Težina 1400g	60,00	50,00
IR BULLET B-256 	3648	Bullet kamera -Čip:Kolor 1/2,8" SONY CMOS, 2,1 Megapiksela HD 1080P (1920x1080) rezolucije, -Optika: varifokal 2,8-12mm -OSD meni: WDR, AE MODE, DAY NIGHT -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.001 Lux @(F1.2,AGC ON), -IC osvetljenje: 6 dioda dometa do 60 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 12W Radna temperatura -10 °C ~+50 °C, IP 66 Dimenzije 290 × 92 × 80 mm, Težina 1400g	63,60	53,00



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
SMOKE DETEKTOR KAMERA B-302 	4419	HDTVI skrivena kamera -Čip: Kolor 1/2,7" Aptina CMOS 2,1 Megapiksel 1080P 3,6mm optika -Osetljivost: 0.01 Lux @(F1.2,AGC ON), -Video izlazi: CVBS/CVI/TVI/AHD -Opšte: Napajanje 12V DC, Potrošnja 550mA Radna temperatura -10 °C ~+50 °C, Dimenzije 119 × 56 mm, Težina 350g	60,00	50,00
PIR SENZOR KAMERA B-303 	4420	HDTVI skrivena kamera -Čip: Kolor 1/2,7" Aptina CMOS 2,1 Megapiksel 1080P 3,7mm optika -Osetljivost: 0.01 Lux @(F1.2,AGC ON), -Video izlazi: CVBS/CVI/TVI/AHD -Opšte: Napajanje 12V DC, Potrošnja 550mA Radna temperatura -10 °C ~+50 °C, Dimenzije 70 × 40 x 119 mm, Težina 350g	60,00	50,00



NAZIV ARTIKLA		Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
BOX DS-2TD2035-HZ8			Čip: Vanadium Oxide Uncooled Focal Plane Detectors Rezolucija: 384x288@25fps Širina područja: 8~14μm Veličina objekta: Čovek 1,8*0,5m, Vozilo 1,4*4,0m Optika: 9,6mm Detekcija vozila: 589m Detekcija čoveka: 192m Podešavanje slike: brightes, AGC, DDE, FFC Kolor paleta: White hot, Black hot, Rainbow, Fusion2, Ironbow1, Ironbow2, Sepia, Color1, Color2, ice fire, Rain,Red hot, Green hot Video kompresija: H.264/MJPEG/MPEG4 Protokoli: IPv4/IPv6,HTTP,HTTPS,802.1X,Qos,FTP,SMTP,UPnP,SNMP,DNS,DDNS,NTP,RTSP,RTCP,RTP,TCP,UDP,IGMP,ICMP,DHCP,PPPoE,Bonj. Interfejs: Alarmni ulazi/izlazi 3/3, Audio ulazi/izlazi 1/1, 1x RJ45, slot za SD karticu do 64GB SMART Funkcije: detekcija provale, prelazak preko zamišljene linije po termalnom senzoru Opšte: Napajanje AC 24V, radna temperatura -40 °C ~+60 °C, IP 66, Dimenzije 502x143x114mm, Težina 10Kg		
	4278			kontakt	
BULLET DS-2TD2235D-50			Čip: Vanadium Oxide Uncooled Focal Plane Detectors Rezolucija: 384x288@25fps Širina područja: 8~14μm Veličina objekta: Vozilo 1,4*4,0m Optika: 50mm Detekcija vozila: 3067m Detekcija čoveka: 1000m Podešavanje slike: brightes, AGC, DDE, FFC Kolor paleta: White hot, Black hot, Rainbow, Fusion2, Ironbow1, Ironbow2, Sepia, Color1, Color2, ice fire, Rain,Red hot, Green hot IR domet: do 150 metara Maksimalana rezolucija: 1920x1080 (dnevni režim), 384x288 (termalna) Video kompresija: H.264/MJPEG/MPEG4 Protokoli: IPv4/IPv6,HTTP,HTTPS,802.1X,Qos,FTP,SMTP,UPnP,SNMP,DNS,DDNS,NTP,RTSP,RTCP,RTP,TCP,UDP,IGMP,ICMP,DHCP,PPPoE,Bonj. Interfejs: Alarmni ulazi/izlazi 7/2, Audio ulazi/izlazi 1/1, 1x RJ45, slot za SD karticu do 64GB, 1x analogni video izlaz, RS-485, SMART Funkcije: detekcija provale, prelazak preko zamišljene linije po termalnom senzoru Opšte: Napajanje AC 24V, 40W max, radna temperatura -40 °C ~+60 °C, IP 66, Zaštia od udara groma Dimenzije 404x174mm, Težina 7Kg		
	4277			kontakt	
SPEED DOME DS-2TD4035D-25/50			Čip: Vanadium Oxide Uncooled Focal Plane Detectors Rezolucija: 384x288 Širina područja: 8~14μm Veličina objekta: Čovek 1,8*0,5m, Vozilo 1,4*4,0m Optika: 25mm/50mm Detekcija vozila: 1533m/3067m Detekcija čoveka: 500m/1000m Podešavanje slike: brightes, AGC, DDE, FFC Kolor paleta: White hot, Black hot, Rainbow, Fusion2, Ironbow1, Ironbow2, Sepia, Color1, Color2, ice fire, Rain,Red hot, Green hot Kruzni opseg: 360° PTZ opcije: 300 preseta, 8 patrol modova, 32 preseta po patrol modu, IR domet: do 150 metara Maksimalana rezolucija: 1920x1080 (dnevni režim), 384x288 (termalna) Video kompresija: H.264/MJPEG/MPEG4 Protokoli: IPv4/IPv6,HTTP,HTTPS,802.1X,Qos,FTP,SMTP,UPnP,SNMP,DNS,DDNS,NTP,RTSP,RTCP,RTP,TCP,UDP,IGMP,ICMP,DHCP,PPPoE,Bonj. Interfejs: Alarmni ulazi/izlazi 7/2, Audio ulazi/izlazi 1/1, 1x RJ45, slot za SD karticu do 64GB, 1x analogni video izlaz, RS-485, SMART Funkcije: detekcija provale, prelazak preko zamišljene linije po termalnom senzoru Opšte: Napajanje AC 24V, radna temperatura -40 °C ~+60 °C, IP 66, Zaštia od udara groma, Dimenzije 266,6x365,2mm, Težina 8Kg		
	4220			kontakt	



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
PanoVu DS-2DP1636Z-D 360°	4275	16 MP PANORAMSKA KAMERA + PTZ KAMERA -8 megapikslnih IP kamera sa 1/1.9" Progressive CMOS senzorom, DARKFIGHTER Max rezolucija panoramne kamere 2x 4096x 1800@30fps; Horizonralni ugao gledanja 360°, vertikalni 78°; Osetljivost 0.002Lux@(F1.8,AGC ON)(Color), 0.0002Lux@(F1.8,AGC ON)(B/W); PTZ kamera: 1/1.9" progressive CMOS; Rezolucije 1920x1080@30fps; Osetljivost Color: 0.005 Lux @ (F1.5, AGC ON), B/W: 0.0005Lux @ (F1.5, AGC ON); Optički zum 36x, digitalni 16x; Kompresija: H.264+/ H.264/ MJPEG/ MPEG4 Interfejsi 1xRJ45, opciono optički Funkcije: True WDR, HLC, 3D DNR; slot za SD karticu do 128GB; 7/2 alarm I/O; audio I/O; IP66 zaštita; Ugrađena zaštita od udara groma; Napajanje 36V DC/ 120W Težina 20kg		kontakt
 				
IP Fisheye DS-2CD6332FWD-IVS	3293	Fisheye IP kamera Čip:1/3" progressive scan CMOS 3Mpx Rezolucija snimanja: 1 x fisheye (2048 x 1536, 25fps) ili 4 x PTZ (800 x 600, 25fps) Multikanalni mod: 1 x fisheye (1536 x 1536, 20fps) i 1 x panoramic (1600 x 1200, 20fps) i 3 x PTZ (800 x 600, 20fps) Osetljivost: 0.1 lux@F1,2, AGC on,WDR Interfejsi: 1x RJ45, 1 x RS-485, Slot za SD karticu do 64GB, Alarmni ulaz/izlaz 1/1, Audio ulaz/izlaz 1/1 Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, IC osvetljenje: Domet IC dioda do 20m Opšte: Napajanje 12V DC,PoE, Potrošnja 11W Radna temperatura -30 °C ~+60 °C, IK10, Dimenzije 164x152.8x45.5mm, Težina 1,4Kg	666,00	555,00
				
IP Fisheye DS-2CD2955FWD-I	5226	Fisheye IP kamera Čip:1/2,5" progressive scan CMOS 5Mpx, Rezolucija snimanja: 2560 x 1920@25fps, Osetljivost: 0.01 lux@F1,2, AGC on, WDR 120dB, Interfejsi: 1x RJ45, Slot za SD karticu do 128GB, Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, IC osvetljenje: Domet IC dioda do 8m, Opšte: Napajanje 12V DC,PoE, Potrošnja 5W, Radna temperatura -10 °C ~+40 °C, Dimenzije 119.9 x 41.2mm, Težina 600g	361,20	301,00
 				





NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
IP BOX DS-2CD4012F-A	3329	Pametna Box kamera Čip:1/3" progressive scan CMOS 1,3Mpx Rezolucija snimanja: 1280*1024@25fps Osetljivost: 0.01 lux@F1.2, AGC on Interfejsi: Audio ulaz/izlaz 1/1, 1x RJ45, 1X RS-485, 1X R-232, Alarmni ulazi/izlazi 1/1, Slot za SD karticu do 64GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour (SIP optional) Mrežni standardi: ONVIF, PSIA, CGI Smart funkcije: Smart Codec, DWDR, 3D DNR, Smart Focus: ABF, Smart VQD, Smart Facial Detection, Smart Audio Detection, Intrusion Detection Opšte: Napajanje 24V AC, 12VDC PoE, Potrošnja 6W Radna temperatura -30 °C ~+60 °C, Dimenzije 69,8×58×148mm, Težina 830g Napomena: Kamera se isporučuje bez optike	230,40	192,00
 				
IP BOX DS-2CD4024F-A	3462	Pametna Box kamera Čip:1/3" progressive scan CMOS 2Mpx Rezolucija snimanja: 1920*1080@25fps Osetljivost: 0.01 lux@F1.2, AGC on Interfejsi: Audio ulaz/izlaz 1/1, 1x RJ45, 1X RS-485, 1X R-232, Alarmni ulazi/izlazi 1/1, Slot za SD karticu do 64GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour (SIP optional) Mrežni standardi: ONVIF, PSIA, CGI Smart funkcije: Smart Codec, DWDR, 3D DNR, Smart Focus: ABF, Smart VQD, Smart Facial Detection, Smart Audio Detection, Intrusion Detection Opšte: Napajanje 24V AC, 12VDC PoE, Potrošnja 6W Radna temperatura -30 °C ~+60 °C, Dimenzije 69,8×58×148mm, Težina 830g Napomena: Kamera se isporučuje bez optike	333,60	278,00
 				
IP BOX DS-2CD4C36FWD-AP	5138	Pametna Box kamera Čip:1/3" progressive scan CMOS 3Mpx Rezolucija snimanja: 2048*1536@20fps Osetljivost: 0.01 lux@F1.2, AGC on Interfejsi: Audio ulaz/izlaz 1/1, 1x RJ45, 1X RS-485, 1X R-232, Alarmni ulazi/izlazi 1/1, Slot za SD karticu do 64GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour (SIP optional) Mrežni standardi: ONVIF, PSIA, CGI Smart funkcije: Smart Codec, DWDR, 3D DNR, Smart Focus: ABF, Smart VQD, Smart Facial Detection, Smart Audio Detection, Intrusion Detection Opšte: Napajanje 24V AC, 12VDC PoE, Potrošnja 6W Radna temperatura -30 °C ~+60 °C Dimenzije 69,8×58×148mm, Težina 830g Napomena: Kamera se isporučuje bez optike. Ultra low light!	450,00	375,00
				
IP BOX DS-2CD4032FWD-A	3497	Pametna Box kamera Čip:1/3" progressive scan CMOS 3Mpx Rezolucija snimanja: 2048*1536@20fps Osetljivost: 0.01 lux@F1.2, AGC on Interfejsi: Audio ulaz/izlaz 1/1, 1x RJ45, 1X RS-485, 1X R-232, Alarmni ulazi/izlazi 1/1, Slot za SD karticu do 64GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour (SIP optional) Mrežni standardi: ONVIF, PSIA, CGI Smart funkcije: Smart Codec, DWDR, 3D DNR, Smart Focus: ABF, Smart VQD, Smart Facial Detection, Smart Audio Detection, Intrusion Detection Opšte: Napajanje 24V AC, 12VDC PoE, Potrošnja 6W Radna temperatura -30 °C ~+60 °C, Dimenzije 69,8×58×148mm, Težina 830g Napomena: Kamera se isporučuje bez optike	434,70	362,25
 				



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
IP CUBE DS-2CD2420F-I 2,8mm		Cube IP kamera Čip:1/3" progressive scan CMOS 2Mpx Rezolucija snimanja: 1920X1080@25fps Osetljivost: 0.07 lux@F12.0, AGC on,DWDR Interfejsi: 1x RJ45, Slot za SD karticu do 128GB, Alarmni ulaz/izlaz 1/1, Integrisan mikrofon Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, Unutrašnja montaža 50m, Spoljašnja montaža 200m IC osvetljenje: Domet IC diode do 10m Opšte: Napajanje 12V DC, 12VDC PoE, Potrošnja 5W, Radna temperatura -30 °C ~+60 °C, Dimenzije 166×91.5×131.3mm, Težina 400g	93,60	78,00
DS-2CD2420F-IW 2,8mm	4906	Model sa WI-FI , domet do 50 metara	103,20	86,00
IP CUBE DS-2CD2442FWD-IW 2,8mm		Cube IP kamera -Čip:1/2,8" progressive scan CMOS 4Mpx -Rezolucija snimanja: 2688 x 1520@20fps -Osetljivost: 0.01 lux@F1.2, AGC on,sa IR, WDR 120dB -Interfejsi: 1x RJ45, Slot za SD karticu do 128GB, Alarmni ulaz/izlaz 1/1, Integrisan mikrofon -Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, -Mrežni standardi: ONVIF, PSIA, CGI, -WI-FI: Unutrašnja montaža 50m, -IC osvetljenje: Domet IC diode do 10m -Opšte: Napajanje 12V DC, 12VDC PoE, -Potrošnja 5W, Radna temperatura -30 °C ~+60°C, -Dimenzije 166×91.5×131.3mm, -Težina 400g	139,32	116,10
IP DOME iDS-2CD6412FWD/C		IP kamera Čip:1/3" progressive scan CMOS 1,3 Mpx Rezolucija snimanja: 1280x960@25fps Osetljivost: 0.01 lux@ (F1.2, AGC on), 0.028lux@ (F2.0, AGC on) 0 Lux sa IR Optika: 2,1mm, WDR 120 dB Interfejsi: Audio ulaz/izlaz 1/1, 1x RJ45, Alarmni ulazi/izlazi 1/1, Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour Mrežni standardi: ONVIF, PSIA, CGI, ISAPI Brojanje ljudi: <i>Ulaz/izlaz ljudi može biti izbrojan, takodje prikazan na displeju i eksportovan. Brojanje ljudi može biti prikazano na displeju u realnom vremenu i eksportovan dnevno/nedeljno/mesечно/godisnje na excel grafikonu (tabeli) i smestiti se na SD card, NAS, Storage server,</i> Opšte: Napajanje 12V DC, Potrošnja 6,5W, Radna temperatura -30 °C ~+60 °C, Dimenzije glavne jedinice: 107,6 x 78 x 33,35 mm, Dimenzije optike: 48,7 x 30,7 x 31,5 ,Težina 615g	kontakt	
IP MINI DOME DS-2CD2542FWD-IS 2.8 mm		Mini dome IP kamera Čip:1/3" progressive scan CMOS 4Mpx Rezolucija snimanja: 2688 x 1520@20fps Osetljivost: 0.01 lux@F1.2, AGC on, WDR 120dB Interfejsi: Audio ulaz/izlaz 1/1, 1x RJ45, Alarmni ulazi/izlazi 1/1, Slot za SD karticu do 128GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, ISAPI IC osvetljenje: Domet IC dioda do 10m Opšte: Napajanje 12V DC, 12VDC PoE, Potrošnja 5W Radna temperatura -30 °C ~+60 °C, IP66, Dimenzije 99,3×96,7×52,8mm, Težina 600g	194,40	162,00



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
IP DOME DS-2CD1121-I 2.8 mm		Dome IP kamera Čip:1/2,8" progressive scan CMOS 2Mpx Rezolucija snimanja: 1920 x 1080@25fps Osetljivost: 0.01 lux@F1.2, AGC on, DWDR Interfejsi:1x RJ45, Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour Mrežni standardi: ONVIF, PSIA, CGI, ISAPI IC osvetljenje: Domet IC dioda do 30m Opšte: Napajanje 12V DC, PoE, Potrošnja 5W Radna temperatura -30 °C ~+60 °C, IP67, IK10, Dimenzije 111x82mm , Težina 500g	81,60	68,00
	4966			
IP DOME DS-2CD1141-I 2.8 mm		Dome IP kamera Čip:1/3" progressive scan CMOS 4Mpx Rezolucija snimanja: 2688x1520@20fps Osetljivost: 0.01 lux@F1.2, AGC on, DWDR Interfejsi:1x RJ45, Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour Mrežni standardi: ONVIF, PSIA, CGI, ISAPI IC osvetljenje: Domet IC diode do 30m Opšte: Napajanje 12V DC, PoE, Potrošnja 5W Radna temperatura -30 °C ~+60 °C, IP67, IK10, Dimenzije 111x82mm, Težina 500g	109,20	91,00
	4967			
IP DOME DS-2CD2120F-IW 2.8mm		Dome IP kamera Čip:1/2,8" progressive scan CMOS 2Mpx Rezolucija snimanja: 1920x1080@25fps Osetljivost: 0.01 lux@F1.2, AGC on, 0 Lux sa IR, WDR 120dB Interfejsi:1x RJ45,Slot za SD karticu do 64GB WI-FI: Unutrašnja montaža 50m, Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour Mrežni standardi: ONVIF, PSIA, CGI, ISAPI IC osvetljenje: Domet IC diode do 30m Opšte: Napajanje 12V DC, PoE, Potrošnja 5W Radna temperatura -30 °C ~+60 °C, IP67, IK10, Dimenzije 110x82mm, Težina 500g	138,00	115,00
  	5439			
IP DOME DS-2CD2142FWD-IW 2.8mm		Dome IP kamera Čip:1/3" progressive scan CMOS 4Mpx Rezolucija snimanja: 2688x1520@20fps Osetljivost: 0.05 lux@F1.2, AGC on, WDR 120dB Interfejsi:1x RJ45,Slot za SD karticu do 128GB WI-FI: Unutrašnja montaža 50m, Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour Mrežni standardi: ONVIF, PSIA, CGI, ISAPI IC osvetljenje: Domet IC diode do 30m Opšte: Napajanje 12V DC, PoE, Potrošnja 5W Radna temperatura -30 °C ~+60 °C, IP67, IK10, Dimenzije 111x82mm, Težina 500g	164,40	137,00
  	5338			
IP DOME DS-2CD2185FWD-I 2.8 mm		Dome IP kamera Čip:1/2.5" progressive scan CMOS 8Mpx Rezolucija snimanja: 3840x2160@20fps Osetljivost: 0.01 lux@F1.2, AGC on, WDR 120dB Interfejsi:1x RJ45,Slot za SD karticu do 128GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour Mrežni standardi: ONVIF, PSIA, CGI, ISAPI IC osvetljenje: Domet IC diode do 30m Opšte: Napajanje 12V DC, PoE, Potrošnja 5W Radna temperatura -30 °C ~+60 °C, IP67, IK10, Dimenzije 111x82mm, Težina 500g	195,30	162,75
  	4805			

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
IP DOME DS-2CD2323G0-I 2.8mm		Dome IP kamera Čip:1/2.8" progressive scan CMOS 2Mpx Rezolucija snimanja: 1920x1080@30fps Osetljivost: 0.01 lux@F1.2, AGC on, 0,028 Lux(F2.0, AGC ON), WDR 120dB Interfejsi: 1x RJ45, Slot za SD karticu do 128GB, reset dugme Smart funkcije: Line crossing detection, intrusion detection, face detection Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour Mrežni standardi: ONVIF, PSIA, CGI , ISAPI IC osvetljenje: Domet IC diode do 30m Opšte: Napajanje 12V DC, PoE, Potrošnja 6W Radna temperatura -30 °C ~+60 °C, IP67, Dimenzije 127,3x95,9mm, Težina 610g	144,00	120,00
 	5369			
IP DOME DS-2CD2355FWD-I 2.8 mm		Dome IP kamera Čip:1/2,9" progressive scan CMOS 5Mpx Rezolucija snimanja: 2944x1656@20fps Osetljivost: 0.01 lux@F11.2, AGC on, WDR 120dB Interfejsi: 1x RJ45, Slot za SD karticu do 128GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, ISAPI IC osvetljenje: Domet EXIR diode do 30m Opšte: Napajanje 12V DC, 12VDC PoE, Potrošnja 5,5W Radna temperatura -30 °C ~+60 °C, IP67, Dimenzije 127x95,9mm, Težina 620g	163,02	135,85
  	4968			
IP DOME DS-2CD2385FWD-I 2.8 mm		Dome IP kamera Čip:1/2,5" progressive scan CMOS 8Mpx Rezolucija snimanja: 3840x2160@20fps Osetljivost: 0.01 lux@F11.2, AGC on, WDR 120dB Interfejsi: 1x RJ45, Slot za SD karticu do 128GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, ISAPI IC osvetljenje: Domet EXIR diode do 30m Opšte: Napajanje 12V DC, 12VDC PoE, Potrošnja 5,5W Radna temperatura -30 °C ~+60 °C, IP67, Dimenzije 127x95,9mm, Težina 620g	204,00	170,00
  	4969			
IP DOME DS-2CD1721FWD-IZ		Dome IP kamera Čip:1/2.8" progressive scan CMOS 2Mpx Rezolucija snimanja: 1920x1080@25fps Osetljivost: 0.01 lux@F1,2, AGC on, 0 Lux with IR, 120dB WDR Optika: motorizovani varifokal od 2,8-12mm Interfejsi: 1x RJ45, Slot za SD karticu do 128GB, Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, ISAPI , IC osvetljenje: Domet IC dioda do 30m Opšte: Napajanje 12V DC, PoE, Potrošnja 11W, Radna temperatura -30 °C ~+60 °C, IP67, IK10, Dimenzije: 141 x 99,9mm, Težina 800g	166,80	139,00
  	5126			
IP DOME DS-2CD1741FWD-IZ 2.8-12mm		Dome IP kamera Čip:1/3" progressive scan CMOS 4Mpx Rezolucija snimanja: 2688x1520@20fps Osetljivost: 0.01 lux@F1,2, AGC on, 0 Lux with IR, 120dB WDR Optika: motorizovani varifokal od 2,8-12mm Interfejsi: 1x RJ45, Slot za SD karticu do 128GB, Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, ISAPI , IC osvetljenje: Domet IC dioda do 30m Opšte: Napajanje 12V DC, PoE, Potrošnja 11W, Radna temperatura -30 °C ~+60 °C, IP67, IK10, Dimenzije: 141 x 99,9mm, Težina 800g	213,60	178,00
  	5127			



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
IP DOME DS-2CD2742FWD-IS	4237	Dome IP kamera Čip: 1/2.7" progressive scan CMOS 4Mpx Rezolucija snimanja: 2688x1520@20fps Osetljivost: 0.01 lux@F1.2, AGC on, WDR 120dB Optika: varifokal od 2,8-12mm Interfejsi: 1x RJ45, Slot za SD karticu do 128GB, Audio ulaz/izlaz 1/1, Alarmni ulaz/izlaz 1/1 Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, IC osvetljenje: Domet IC dioda do 30m Opšte: Napajanje 12V DC, PoE, Potrošnja 5,5W Radna temperatura -30 °C ~+60 °C, IP67, Dimenzije: 141 x 99,9mm, Težina 800g	230,40	192,00
  				
IP DOME DS-2CD4132FWD-IZ	3241	Pametna IP dome kamera Čip: 1/3" progressive scan CMOS 3Mpx Rezolucija snimanja: 2048 x 1536@20fps Osetljivost: 0.14 lux@F1.2, AGC on Optika: varifokal od 2,8-12mm Interfejsi: Audio ulaz/izlaz 1/1, 1x RJ45, 1X RS-485, 1X R-232, Alarmni ulazi/izlazi 1/1, Slot za SD karticu do 64GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour (SIP optional) Mrežni standardi: ONVIF, PSIA, CGI Smart funkcije: Smart Codec, 120dB WDR, 3D DNR, Smart Focus: Motorized VF lens, Smart VQD, Smart Facial Detection, Smart Audio Detection, Intrusion Detection Opšte: Napajanje 12VDC, PoE, Potrošnja 6,5W Radna temperatura -30 °C ~+60 °C, IK10 Dimenzije 140 x 121.8mm, Težina 1400g	543,60	453,00
 				
IP DOME DS-2CD4332FWD-IZ	3722	Pametna IP dome kamera Čip: 1/3" progressive scan CMOS 3Mpx Rezolucija snimanja: 2048 x 1536@20fps Osetljivost: 0.1 lux@F1.2, AGC on Optika: varifokal od 2,8-12mm Interfejsi: 1x RJ45, Slot za SD karticu do 64GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour (SIP optional) Mrežni standardi: ONVIF, PSIA, CGI Smart funkcije: Smart Codec, 120dB WDR, 3D DNR, Smart Focus: Motorized VF lens, Smart VQD, Smart Facial Detection, Smart Audio Detection, Intrusion Detection Opšte: Napajanje 24V AC, PoE, Potrošnja 12W Radna temperatura -30 °C ~+60 °C, IP66 Dimenzije 159.8 x 146 mm, Težina 2100g	621,60	518,00
 				



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
IP BULLET DS-2CD1021-I 4.0 mm	5195	Bullet kamera Čip:1/2,8" progressive scan CMOS 2Mpx Rezolucija snimanja: 1920 x 1080@25fps Osetljivost: 0.01 lux@F12.0, AGC on, Interfejsi: 1x RJ45, Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, IC osvetljenje: Domet IC dioda do 30m Opšte: Napajanje 12V DC, 12VDC PoE, Potrošnja 5W Radna temperatura -30 °C ~+60 °C, IP67, Dimenzije 69 x 172,7 x 66mm, Težina 500g	81,60	68,00
IP BULLET DS-2CD2020F-I 4.0 mm	3919	Bullet kamera Čip:1/2,8" progressive scan CMOS 2Mpx Rezolucija snimanja: 1920 x 1080@25fps Osetljivost: 0.01 lux@F12.0, AGC on, Interfejsi: 1x RJ45, Slot za SD karticu do 128GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, IC osvetljenje: Domet IC dioda do 30m Opšte: Napajanje 12V DC, 12VDC PoE, Potrošnja 5W Radna temperatura -30 °C ~+60 °C, IP66, Dimenzije 70 x 157 x 62mm, Težina 500g	90,00	75,00
IP BULLET DS-2CD1041-I 4.0 mm	5199	Bullet kamera Čip:1/2,8" progressive scan CMOS 4Mpx Rezolucija snimanja: 2688 x 1520@20fps Osetljivost: 0.01 lux@F12.0, AGC on, Interfejsi: 1x RJ45, Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, IC osvetljenje: Domet IC dioda do 30m Opšte: Napajanje 12V DC, 12VDC PoE, Potrošnja 5W Radna temperatura -30 °C ~+60 °C, IP67, Dimenzije 69 x 172,7 x 66mm, Težina 500g	110,40	92,00
IP BULLET DS-2CD2T22WD-I5 4.0 mm	4232	Bullet kamera Čip:1/2,8" progressive scan CMOS 2Mpx Rezolucija snimanja: 1920 x 1080@25fps Osetljivost: 0.01 lux@F12.0, AGC on, WDR 120dB Interfejsi: 1x RJ45, Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, ISAPI IC osvetljenje: Domet EXIR diode do 50m Opšte: Napajanje 12V DC,PoE, Potrošnja 7,5W Radna temperatura -30 °C ~+60 °C, IP67, Dimenzije 299 x 86 x 85mm, Težina 1200g	130,80	109,00



EXIR



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
IP BULLET DS-2CD2T55FWD-I5 4.0 mm   	5002	Bullet IP kamera Čip:1/2,9" progressive scan CMOS 5Mpx Rezolucija snimanja: 2944 x 1656@20fps Osetljivost: 0.01 lux@F12.0, AGC on, WDR 120dB Interfejsi: 1x RJ45, Slot za SD karticu do 128GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, ISAPI IC osvetljenje: Domet EXIR diode do 50m Opšte: Napajanje 12V DC, 12VDC PoE, Potrošnja 7,5W Radna temperatura -30 °C ~+60 °C, IP66, Dimenzije 299 x 86 x 85mm, Težina 1200g	163,20	136,00
IP BULLET DS-2CD2T85FWD-I8 4.0 mm    	4807	Bullet IP kamera Čip:1/2.5" progressive scan CMOS 8Mpx Rezolucija snimanja: 3840 x 2160@20fps Osetljivost: 0.01 lux@F12.0, AGC on, WDR 120dB Interfejsi: 1x RJ45, Slot za SD karticu do 128GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, ISAPI IC osvetljenje: Domet EXIR diode do 80m Opšte: Napajanje 12V DC, 12VDC PoE, Potrošnja 10W Radna temperatura -30 °C ~+60 °C, IP67, Dimenzije 299 x 86 x 85mm, Težina 1200g	246,00	205,00
IP BULLET DS-2CD1621FWD-IZ  	5124	Bullet IP kamera Čip:1/2.8" progressive scan CMOS 2Mpx Rezolucija snimanja: 1920x1080@25fps Osetljivost: 0.01 lux@F1,2, AGC on, WDR 120dB Optika: motorizovani varifokal od 2,8-12mm Interfejsi: 1x RJ45, Slot za SD karticu do 128GB, Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, IC osvetljenje: Domet IC dioda do 30m Opšte: Napajanje 12V DC, PoE, Potrošnja 11W Radna temperatura -30 °C ~+60 °C, IP67, Dimenzije: 91,6x105x294,5mm, Težina 1200g	164,40	137,00
IP BULLET DS-2CD1641FWD-IZ 2.8-12mm   	5355	Bullet IP kamera Čip:1/3" progressive scan CMOS 4Mpx Rezolucija snimanja: 2688x1520@20fps Osetljivost: 0.01 lux@F1,2, AGC on, 0 Lux sa IR, WDR 120dB Optika: motorizovani varifokal od 2,8-12mm Interfejsi: 1x RJ45, Slot za SD karticu do 128GB, Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour Mrežni standardi: ONVIF, PSIA, CGI, ISAPI IC osvetljenje: Domet IC dioda do 30m, Opšte: Napajanje 12V DC, PoE, Potrošnja 5-11W Radna temperatura -30 °C ~+60 °C, IP67, Dimenzije: 91,6x105x294,5mm, Težina 1200g	220,80	184,00
IP BULLET DS-2CD2685FWD-IZS    	4890	Bullet IP kamera Čip:1/2.5" progressive scan CMOS 8Mpx Rezolucija snimanja: 3840 x 2160@20fps Osetljivost: 0.01 lux@F12.0, AGC on, WDR 120dB Optika: motorizovan varifokal od 2,8-12mm Interfejsi: 1x RJ45, Slot za SD karticu do 128GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, ISAPI IC osvetljenje: Domet EXIR diode do 50m Opšte: Napajanje 12V DC, 12VDC PoE, Potrošnja 10W Radna temperatura -30 °C ~+60 °C, IP67, Dimenzije 299 x 86 x 85mm, Težina 1200g	366,00	305,00



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
IP BULLET DS-2CD4232FWD-IS	3872	Pametna IP bullet kamera Čip:1/3" progressive scan CMOS 3Mpx Rezolucija snimanja: 2048 x 1536@20fps Osetljivost: 0.1 lux@F1.2, AGC on Optika: varifokal od 2,8-12mm Interfejsi: Audio ulaz/izlaz 1/1, 1x RJ45, 1X RS-485, 1X R-232, Alarmni ulazi/izlazi 1/1, Slot za SD karticu do 64GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour (SIP optional) Mrežni standardi: ONVIF, PSIA, CGI Smart funkcije: Smart Codec, 120dB WDR, 3D DNR, Smart Focus: Motorized VF lens, Smart VQD, Smart Facial Detection, Smart Audio Detection, Intrusion Detection, Smart grejac Opšte: Napajanje 12V DC, PoE, Potrošnja 12W Radna temperatura -30 °C ~+60 °C, IP66 Dimenzije 98 x 105 x 328 mm, Težina 1700g	544,80	454,00
 				
IP BULLET DS-2CD4AC5F-IZHS	4279	Pametna IP bullet kamera Čip:1/1,7" progressive scan CMOS 12Mpx Rezolucija snimanja: 4000 x 3000@15fps Osetljivost: 0.01 lux@ (F1.2, AGC on), 0.014lux@ (F1.4, AGC on) 0 Lux sa IR Optika: varifokal od 2,8-12mm, motorizovana Interfejsi: Audio ulaz/izlaz 1/1, 1x RJ45, Grejač, Alarmni ulazi/izlazi 1/1, 1x BNC, Slot za SD karticu do 128GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour Mrežni standardi: ONVIF, PSIA, CGI, ISAPI Smart funkcije: Smart Codec, 3D WDR, 3D DNR, Smart Focus: Motorized VF lens, Smart VQD, Smart Facial Detection, Smart Codec, Smart Audio Detection, Intrusion Detection Opšte: Domet IR dioda do 50m, Napajanje 12V DC, PoE, Potrošnja 18W Radna temperatura -30 °C ~+60 °C, IP67, Dimenzije 100 x 103 x 311 mm, Težina 2000g	1.304,40	1.087,00
  				
IP BULLET DS-2CD4A25FWD-IZHS	4127	Pametna IP bullet kamera Čip:1/2,8" progressive scan CMOS 2Mpx Rezolucija snimanja: 1920 x 1080@50fps Osetljivost: 0.005 lux@F1.2, AGC on, 0.007lux@ (F1.4, AGC on) 0 Lux sa IR 0 Lux sa IR Optika: varifokal od 2,8-12mm, motorizovana Interfejsi: Audio ulaz/izlaz 1/1, 1x RJ45, 1x BNC, Grejač, Alarmni ulazi/izlazi 1/1, Slot za SD karticu do 128GB Protokoli: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Mrežni standardi: ONVIF, PSIA, CGI, ISAPI Smart funkcije: Smart Codec, 140dB WDR, HLC, 3D DNR, Smart Focus: Motorized VF lens, Smart VQD, Smart Facial Detection, Smart Codec, Smart Audio Detection, Intrusion Detection, Opšte: Domet IR dioda do 50m, Napajanje 12V DC, PoE, Potrošnja 11W R. temperatura -30 °C ~+60 °C, IP67, Dimenzije 100 x 103 x 311 mm, Težina 2000g	760,80	634,00
  				



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena (racun bez PDV)
IP SPEED DOME DS-2DE7120IW-AE		Motorizovana upravljiva kupolna kamera. Čip:Kolor 1/3" progressive scan CMOS 1,3 Mpx DWDR Rezolucija snimanja: 1280 x 960@60fps Optika: 20x optički zum, 16x digitalni zum Osetljivost: 0.05 Lux @(F1.6,AGC ON), Interfejsi: 1x RJ45, RS-485, Alarm ulaz/izlaz 2/1, Audio ulaz/izlaz 1/1, slot za SD karticu do 128GB PTZ: pelco P,pelco D protokoli, 256 preset pozicija, 8 patrol moda, rotacija 360°, 3D inteligentno pozicioniranje Opšte: Napajanje 24V AC, Potrošnja 40W, HI-PoE Zaštita od udara groma, domet IC dioda 150m Radna temperatura -30 °C ~+60 °C, IP66, Težina 4,5Kg	588,00	490,00
	4927			
IP SPEED DOME DS-2DE4220IW-DE		Motorizovana upravljiva kupolna kamera. Čip:Kolor 1/2,8" progressive scan CMOS 2Mpx Rezolucija snimanja: 1920 x 1080@25fps Optika: 20x optički zum, 16x digitalni zum Osetljivost: 0.05 Lux @(F1.6,AGC ON), Interfejsi: 1x RJ45, Audio ulaz/izlaz 1/1, slot za SD karticu do 128GB PTZ: pelco P,pelco D protokoli, 300 preset pozicija, 8 patrol moda, rotacija 360° Opšte: Napajanje 12V DC, Potrošnja 20W Zaštita od udara groma, domet IC dioda 100m Radna temperatura -30 °C ~+60 °C Težina 2Kg	522,00	435,00
 	5224			
IP SPEED DOME DS-2DE7220IW-AE		Motorizovana upravljiva kupolna kamera. Čip:Kolor 1/2,8" progressive scan CMOS 2Mpx DWDR Rezolucija snimanja: 1920 x 1080@25fps Optika: 20x optički zum, 16x digitalni zum Osetljivost: 0.05 Lux @(F1.6,AGC ON), Interfejsi: 1x RJ45, RS-485, Alarm ulaz/izlaz 2/1, Audio ulaz/izlaz 1/1, slot za SD karticu do 128GB PTZ: pelco P,pelco D protokoli, 256 preset pozicija, 8 patrol moda, rotacija 360°, 3D inteligentno pozicioniranje Opšte: Napajanje 24V AC, Potrošnja 40W, HI-PoE Zaštita od udara groma, domet IC dioda 150m Radna temperatura -30 °C ~+60 °C, IP66, Težina 4,5Kg	717,60	598,00
	4530			
IP SPEED DOME DS-2DE7230IW-AE		Motorizovana upravljiva kupolna kamera. Čip:Kolor 1/2,8" progressive scan CMOS 2Mpx DWDR Rezolucija snimanja: 1920 x 1080@25fps Optika: 30x optički zum, 16x digitalni zum Osetljivost: 0.05 Lux @(F1.6,AGC ON), Interfejsi: 1x RJ45, RS-485, Alarm ulaz/izlaz 2/1, Audio ulaz/izlaz 1/1, slot za SD karticu do 128GB PTZ: pelco P,pelco D protokoli, 256 preset pozicija, 8 patrol moda, rotacija 360°, 3D inteligentno pozicioniranje Opšte: Napajanje 24V AC, Potrošnja 40W, HI-PoE Zaštita od udara groma, domet IC dioda 150m Radna temperatura -30 °C ~+60 °C, IP66, Težina 4,5Kg	866,40	722,00
	5192			

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
IP SPEED DOME DS-2DE7530IW-AE 	5131	Motorizovana upravljiva kupolna kamera. Čip:Kolor 1/1.9" progressive scan CMOS 5Mpx, WDR 92dB Rezolucija snimanja: 2592 x 1944@25fps Optika: 30x optički zum, 16x digitalni zum Osetljivost: 0.005 Lux @(F1.6,AGC ON), Interfejsi: 1x RJ45, RS-485, Alarm ulaz/izlaz 2/1, Audio ulaz/izlaz 1/1, slot za SD karticu do 128GB PTZ: pelco P,pelco D protokoli, 256 preset pozicija, 8 patrol moda, rotacija 360°, 3D inteligentno pozicioniranje Opšte: Napajanje 24V AC, Potrošnja 40W, HI-PoE Zaštita od udara groma, dolet IC dioda 150m Radna temperatura -30 °C ~+60 °C, IP66, Težina 4,5Kg	1.290,00	1.075,00
IP SPEED DOME DS-2DF8836I5V-AELW  4K ULTRA HD 	4280	Pametna motorizovana upravljiva kupolna kamera. Čip:Kolor 1/1,9" CMOS,progressive scan CMOS 8Mpx, Rezolucija snimanja: 4096 x 2160@25fps Optika: 36x optički zum, 16x digitalni zum Osetljivost: 0.02 Lux @(F1.5,AGC ON), WDR 120dB Interfejsi: 1x RJ45, RS-485 pelco P,pelco D, Audio ulaz/izlaz 1/1, Alarmni ulaz/izlaz 1/1, H.264/MJPEG Slot za SD karticu do 128GB Smart funkcije: Panorama, 3D inteligentno pozicioniranje, Tri strima, Pametno praćenje, odmagljivanje, brisač za čišćenje, PTZ: pelco P,pelco D protokoli, 256 preset pozicija, 8 patrol modova, Opšte: Napajanje 24V AC, Potrošnja 52W, Zaštita od udara groma Domet IC dioda 150m Radna temperatura -30 °C ~+60 °C, IP66, Težina 5,5Kg	kontakt	





NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
Plafonski nosač				
<u>DS-1663ZJ</u>				
	4601	Plafonski nosač dužine 5,7cm za PTZ kamere HIKVISION	17,16	14,30
Plafonski nosač				
<u>DS-1661ZJ</u>				
	4600	Plafonski nosač dužine 20cm za PTZ kamere HIKVISION	42,90	35,75
Zidni nosač				
<u>DS-1602ZJ</u>				
	3711	Zidni nosač za PTZ kamere HIKVISION	24,00	20,00
Zidni nosač sa adapterom				
<u>DS-1602ZJ CORNER</u>				
	3712	Zidni ugaoni nosač sa adapterom za PTZ kamere HIKVISION	48,30	40,25
DS-1601ZJ - BOX KUĆIŠTE SA NOSAČEM				
<u>DS-1602ZJ</u>				
	3518	Nazidno kućište za PTZ kamere sa nosačem. IP 66 , Dimenzije 310 (V) x 175 (Š) x 90 (D) mm , Težina 2,5 kg	108,00	90,00
DŽOJSTIK ZA PTZ KAMERE				
<u>DS-1005KI</u>				
	4126	Tastatura za kontrolu PTZ kamera -Podržani sistemi: Windows XP/7/8/8.1/10 -Interfejsi: USB 2.0, DirectX -Kontrola: Džojstik (upravljivost 3 ose, rotacija, zoom) -Tasteri: 15 programibilnih tastera -Napajanje: 5V DC kroz USB -Petrošnja: < 5W -Radna temperatura -10 °C ~ +55 °C -Dimenzije: 167x177,5x116mm	264,00	220,00
IP TASTATURA				
<u>DS-1100KI</u>				
	1601	7" TFT ergonomski dizajniran ekran osetljiv na dodir sa rezolucijom 800x480 Speed dome, video dekodir & DVR kontrola 1-ch HD video stream dekodiranje 1080p Podrška za 15 korisnika, sa mogućnošću upravljanja sa 256 uređaja po svakom korisniku Kompatibilan sa DVR/DVS, matrix, network camera/dome, PC/DVR itd. Audio ulaz (1-ch, 3.5m) / Audio izlaz (1-ch, 3.5m), 1 RJ45, 1 RS-232, 1 RS-485, 1 USB2.0 (za skladištenje podataka i nadogradnju uređaja), 12V DC	1.142,40	952,00



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
OBJEKTIV TVO309-IR 	1517	Auto iris, Vari-focal IR Lens, Dužina otvora blende F1.2-C, Postolje CS, Format 1/3", Minimalna radna udaljenost 0.2m, Iris kontrola DC, Radna udaljenost do 20m	17,40	14,50
OBJEKTIV TV2713D-IR 	1518	Auto iris, Vari-focal IR Lens, Dužina fokusa 2.7~13 mm, Raspon otvora blende F1.3-C, Postolje CS, Format 1/3", Minimalna radna udaljenost 0.3m, Iris kontrola DC, Radna udaljenost do 30m	17,40	14,50

MEGAPIKSELNI OBJEKTIVI



NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
OBJEKTIV M13VG308 	2964	Megapikselni varifokalni objektiv, automatska blenda, 3.0~8.0 mm, ugao 92.5°~35.4°, F1.0~360, 1/3"	132,48	110,40


ILUMINATORI

ILLUMINATOR WEATHERPROOF IR B-305 	1403	IR LED: 8 LED DIODA IR udaljenost: 80 m Dimenzije: 150(L)*120(H)* 88(W) mm Snaga: 12V DC potrošnja 1500mA Ugao pokrivanja: 60 °C Težina: 860g	72,00	60,00
---	------	--	-------	-------

HIKVISION PoE SWITCHEVI

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
DS-3E0105P-E 	4818	4 x 10/100 Mbps Auto MDX PoE 1 x 10/100/1000 Mbps 4kV zaštita od prenapona PoE budžet 58W Dimenzije: 132 x 93.3 x 27.6mm	69,60	58,00
DS-3E0109P-E 	4819	8 x 10/100 Mbps Auto MDX PoE 1 x 10/100/1000 Mbps 4kV zaštita od prenapona PoE budžet 123W Podržava 802.3 AF/AT standarde do 30W snage po portu Dimenzije: 235 x 103 x 27mm	190,80	159,00
DS-3E0318P-E 	4820	16 x 10/100 Mbps Auto MDX PoE 2 x 1000 Mbps Combo port 4kV zaštita od prenapona PoE budžet 230W Podržava 802.3 AF/AT standarde do 30W snage po portu Dimenzije: 440 x 285 x 43mm	423,60	353,00

PRATEĆA OPREMA

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
CCTV MERNI INSTRUMENT BMI-S 	2634	Novi CCTV merni instrument. Podržava sledeće tehnologije: HDTVI, HDCVI, AHD, CVBS. Monitor 3,5" TFT-LCD, BNC video ulaz i izlaz, RS-485, UTP kabl tester (za proveru ispravnosti UTP kabla), Izlazno napajanje 12v,1A za napajanje kamere, Audio ulaz. Napajanje DC 5V, baterija 3,7V lithium polymer 3000mAh, Punjenje baterije od 3 do 4 sata, Radna operativnost posle punjenja je 11 sati. Dimenzije 194mm x 112mm x 48mm, Težina 540g	241,50	201,25
MIKROFON SA KABLOM LY-501C 	2584	Audio modul sa izvedenim konektorima. Napajanje 12 V DC	3,97	3,31
MIKROFON PLASTICNI LY-502B 	2583	Audio modul plastični sa trimenom. Napajanje 12 V DC	6,00	5,00
MIKROFON METALNI LY-506 	1937	Audio modul metalni sa trimenom. Napajanje 12 V DC	10,00	8,33
PASIVNI UTP PREDAJNIK UTP-202-HD (par) 	3632	Univerzalni video balun. Podržava analognu tehnologiju (400m); HDTVI (720p/1080p :200m); AHD (960H/720p :300m); HDCVI (720p :400m). Propusni opseg 0~50MHz. Impendansa : muški BNC 75ohms, UTP kabl 100ohms. Preporučena kategorija kabla cat 5e/6 . UTP kablovi u standardu 24-16 AWG (0,5-1,31mm). Impendansa 100±20Ω. Temperaturni uslovi 0-55C° . Relativna vlažnost 0-95%	6,90	5,75
PASIVNI UTP PREDAJNIK DS-1H18 (par) 	3502	Pasivni video balun za HD-TVI kamere. Podržava analognu tehnologiju do (400m); HD-TVI, HDCVI, AHD do (200m) prenosne daljine. Preporučena kategorija kabla Cat5/6.	7,20	6,00
HDMI EXTENDER 30M T-502 	4053	Prenos signala preko dva UTP kabla na 30 metara. Napajanje 5V.	25,00	21,00

KUĆIŠTA I NOSAČI

KUĆIŠTE ZA SPOLJNU
MONTAŽU
BK-1GH



2689

Kućište za spoljnu montažu sa grejačem i ventilatorom, nadstrešnica, termozaštićeno, Dimenzije: 260x100x75mm, 230Vac, bež boja, bočno otvaranje. Bez nosača.

31,04

25,87

NOSAČ KUĆIŠTA
BNS-1



2688

Nosač metalni sa prolazom za kabl, bež boje. Namenjen za kućište BK-1GH

12,00

10,00

NOSAČ ZA UNUTRAŠNJU
MONTAŽU
BNP-1



2685

Nosač box kamere plastični, bež boje.

3,96

3,30

NOSAČ ZA UNUTRAŠNJU
MONTAŽU UGAONI
BNP-2



2686

Nosač ugaoni, plastični, dome kamere, bež boje. Dimenzije prečnika 90mm

6,90

5,75

NOSAČ ZA SPOLJNU
MONTAŽU UGAONI
BNM-1



2687

Nosač ugaoni metalni, dome kamere, bež boje. Dimenzije prečnika 130mm

12,00

10,00

NOSAČ ZA BEAR DOME
KAMERE
BA-1S



3633

Metalni nosač za Dome kamere, tamnosive boje. Dimenzije prečnika 45mm i dubine 45mm.

6,00

5,00

NOSAČ ZA BEAR DOME
KAMERE
BA-2S




3635

Metalni nosač za Dome kamere, tamnosive boje. Dimenzije prečnika 120mm i dubine 45mm.

6,90

5,75

NOSAČ ZA KAMERE
BA-2B



4741

Metalni nosač za Dome kamere, bele boje. Dimenzije prečnika 120mm i dubine 40mm.

7,80

6,50

NOSAČ ZA KAMERE
BA-5B



4742

Univerzalna metalna razvodna kutija za smestanje kablova i napajanja za kamere, vodootporna. Prečnik je 135mm, sa dva uvodnika za kablove.

16,80

14,00

NOSAČ ZA KAMERE
BA-4B



5152

Univerzalna metalna razvodna kutija za smestanje kablova i napajanja za kamere, vodootporna. Dimenzije:135x135x58mm, sa dva uvodnika za kablove.

18,00

15,00

NOSAČ ZA BEARBULLET
KAMERE
BA-3B



3636

Metalni nosač za Bullet kamere, bele boje. Dimenzije :100mm(V) x 130mm(Š) x35mm(D)

7,20

6,00

NOSAČ ZA BEAR BULLET
KAMERE
BA-3S



3637

Metalni nosač za Bullet kamere, tamnosive boje. Dimenzije :100mm(V) x 130mm(Š) x35mm(D)

7,20

6,00

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
KUĆIŠTE ZA SPOLJNU MONTAŽU DS-1313HZ 	1974	Kućište za spoljnu montažu sa grejačem i ventilatorom, nadstrešnica, termozaštićeno, Dimenzije: 458×122.3×140.6 mm, 230Vac, bež boja. Radna temperatura -40°C~70°C. IP66 Napajanje 220 V	86,24	71,87
NOSAČ KUĆIŠTA DS-1313HZ, DS-1213ZJ 	1975	Aluminijumski nosač u boji kućišta. Dimenzije: 304×71×100 mm	15,52	12,93
NOSAČ KAMERE ZA SPOLJNU MONTAŽU DS-1260ZJ 	3761	Razvodna kutija za smestanje kablova i napajanja za kamere serije DS-2CE15x2P-VFIR3, DS-2CD22x2-I i DS-2CD26x2F-I H	19,20	16,00

KUĆIŠTA I NOSAČI

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
UNIVERZALNI NOSAČ KAMERE DS-1275ZJ 	4349	Univerzalni metalni nosač za montažu kamere na stub. Širina stuba mora biti od 67~127mm	24,00	20,00
ZIDNI NOSAČ DOME KAMERE DS-1258ZJ 	3864	Zidni plastični nosač za dome kamere. Podržava serije kamera: DS-2CD21XXF-I (S)	8,40	7,00
ZIDNI NOSAČ DOME KAMERE DS-1272ZJ-110TRS 	4705	Zidni metalni nosač za dome kamere. Podržava serije kamera: DS-2CC55X2P(N)-IR, DS-2CE55X2P(N), DS-2CC5132P(N)-IRP	18,00	15,00
ZIDNI NOSAČ DOME KAMERE DS-1273ZJ-135 	3705	Zidni metalni nosač za dome kamere. Podržava serije kamera: DS-2CC52X1P(N)-VP, DS-2CC52X1P(N)-AVPIR2, DS-2CD2712F-I(S), DS-2CD2732F-I(S)	20,40	17,00
ZIDNI NOSAČ DOME KAMERE DS-1273ZJ-130 	5353	Zidni metalni nosač za dome kamere. Podržava serije kamera: DS-2CD7X3PF(NF)-E(I)(Z),DS-2CD793PFWD-E(I)(Z) DS-2CD793NFWD-E(I)(Z),DS-2CD7X4FWD-E(I)(Z) DS-2CD7XXF-E(I)(Z),DS-2CD783F-EP DS-2CD4112F-(I),DS-2CD4112FWD-(I) DS-2CD4124F-(I),DS-2CD4132FWD-(I)	24,00	20,00
NOSAČ KAMERE DS-1259ZJ 	4888	Plastični plafonski nosač za kamere serije DS-2CDXX2F-I	4,80	4,00

KUĆIŠTA I NOSAČI

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
NOSAČ KAMERE DS-1280ZJ-DM18				
	4732	Metalni nosač za kamere serije DS-2CD21xxF-I	14,83	12,36
NOSAČ KAMERE DS-1280ZJ-XS				
	4838	Univerzalna metalna razvodna kutija za smestanje kablova i napajanja za kamere. Prečnik je 100mm	14,40	12,00
NOSAČ KAMERE DS-1280ZJ-S				
	5113	Univerzalna metalna razvodna kutija za smestanje kablova i napajanja za kamere. Prečnik je 137mm	19,20	16,00
NOSAČ KAMERE DS-1280ZJ-M				
	4434	Univerzalna metalna razvodna kutija za smestanje kablova i napajanja za kamere. Prečnik je 157mm	20,40	17,00

KONEKTORI I ALATI

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
F KONEKTOR na krimp RG59				
	1796	F konektor za RG59 kabl . Pakovanje 100 kom.	0,15	0,13
F KONEKTOR na krimp RG6				
	2559	F konektor za RG6 kabl . Pakovanje 100 kom.	0,11	0,09
F KONEKTOR KOMPRESIONI RG59 XL				
 	1624	Profesionalni PPC F konektor za RG59 kabl . Pakovanje 50 kom.	0,47	0,39
F KONEKTOR KOMPRESIONI RG6 XL				
 	1625	Profesionalni PPC F konektor za RG6 kabl . Pakovanje 50 kom.	0,43	0,36
F KONEKTOR KOMPRESIONI RG11 XL				
 	1627	Profesionalni PPC F konektor za RG11 kabl .	2,96	2,47
RF METALNI G MUŠKI				
	4448	RF metalni G muški (UGAONI) konektor Pakovanje 100 kom.	0,34	0,29
RCA MUŠKI-F ŽENSKI				
	4446	RCA muški - F ženski konektor Pakovanje 100 kom.	0,41	0,35

KONEKTORI I ALATI

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
F NASTAVAK				
	3300	F nastavak Ženski - Ženski Pakovanje 100 kom	0,18	0,15
BNC NASTAVAK				
	4447	BNC konektor. Nastavak ženski-ženski. Pakovanje 100 kom.	0,39	0,32
BNC NA KRIMP RG59				
	2534	BNC konektor za RG59 kabl na krimp. Pakovanje 100 kom.	0,55	0,46
BNC MUŠKI- F ŽENSKI				
	1795	BNC konektor muški F ženski. Pakovanje 100 kom.	0,49	0,41
BNC NA LEMLJENJE SA ŠRAFOM				
	3299	BNC konektor muški sa šrafom. Pakovanje 100 kom.	0,29	0,24
BNC NA LEMLJENJE				
	2560	BNC konektor muški na lemljenje. Pakovanje 100 kom.	0,29	0,24
ALAT ZA KRIMP RG59,RG6, RG11				
	3302	Alat za krimpovanje RG59,RG6,RG11 konektora	48,00	40,00
STRIPER ZA KABLOVE RG59,RG6				
	3301	Alat za stripovanje RG59,RG6 kablova	17,24	14,37
ALAT KOMPRESIONI, ZA RG59, RG6				
	1629	Profesionalni PPC alat za kompresovanje kompresionih F konektora RG59,RG6 XL oznake.	37,92	31,60
ALAT KOMPRESIONI, ZA RG59,RG6,RG11				
	3796	Profesionalni PPC alat za kompresovanje kompresionih F konektora RG59,RG6,RG11 XL oznake.	51,74	43,12

KABLOVI

NAZIV ARTIKLA	Kat.br.	Karakteristike		Cena (racun bez PDV)	Cena -20%
<u>ALARMNI KABL</u> <u>6x0,25 100m</u> 	1429	Pakovanje 100m. Bela boja.		0,230	0,195
<u>KOAKSIJALNI KABL</u> <u>RG59 100m</u> 	1867	Pakovanje 100m. Crna boja.		0,250	0,223
<u>KOAKSIJALNI KABL LSZH</u> <u>RG59 305m</u>  	2780	Pakovanje 305m. Crna boja. Motalica. Halogen free.		0,313	0,278
<u>KOAKSIJALNI KABL</u> <u>RG59 305m</u>  	0089	Pakovanje 305m. Crna boja Motalica.		0,225	0,200
<u>KOAKSIJALNI KABL</u> <u>RG59+2X0,50 E1 100m</u> 	1800	Koaksijalni kabl RG59 + napojni 2x0,50 Pakovanje 100m Crna boja.		0,375	0,340
<u>KOAKSIJALNI KABL</u> <u>RG59+2X0,75 100m</u> 	4670	Koaksijalni kabl RG59 + napojni 2x0,75 Pakovanje 100m Crna boja.		0,475	0,420
<u>KOAKSIJALNI KABL</u> <u>RG59+2X0,50 E1 305m</u> 	1879	Koaksijalni kabl RG59 + napojni 2x0,50 Pakovanje 305m Crna boja Motalica.		0,400	0,374
<u>KOAKSIJALNI KABL</u> <u>RG59+2X0,75 305m</u>  	0485	Koaksijalni kabl RG59 + napojni 2x0,75 Pakovanje 305m Crna boja Motalica.		0,500	0,433
<u>KOAKSIJALNI KABL</u> <u>RG59+2X0,75 305m LSZH</u>  	1047	Koaksijalni kabl RG59 + napojni 2x0,75 Pakovanje 305m Crna boja Motalica Halogen free.		0,650	0,597



KABLOVI

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
KOAKSIJALNI KABL RG59+UTP Cat5 305m  	1044	Koaksijalni kabl RG59 + UTP Cat5 Pakovanje 305m Crna boja Motalica.	0,650	0,583
KOAKSIJALNI KABL RG59+UTP Cat5 305m  	0482	Koaksijalni kabl RG6 TRI-SHIELD Pakovanje 305m Bela boja Motalica.	0,188	0,166
DS-1LN5E-E/E MREŽNI KABL UTP Cat5 Cu 305m   	5045	Mrežni kabl UTP Cat5 Cu Pakovanje 305m Siva boja Motalica.	0,360	0,300
DS-1LN6-UE-W MREŽNI KABL UTP Cat6 Cu 305m   	5046	Mrežni kabl UTP Cat6 Cu Pakovanje 305m Siva boja Motalica.	0,436	0,363
MREŽNI KABL UTP Cat5 CCA 305m  	2625	Mrežni kabl UTP Cat5 CCA Pakovanje 305m Siva boja Motalica.	0,150	0,130
MREŽNI KABL UTP Cat5 CCAG-A1 305m  	2624	Mrežni kabl UTP Cat5 CCAG-A1 Pakovanje 305m Plava boja Motalica.	0,225	0,182
MREŽNI KABL UTP Cat5 Cu 305m  	2622	Mrežni kabl UTP Cat5 Cu Pakovanje 305m Plava boja Motalica.	0,338	0,300
MREŽNI KABL UTP Cat6 Cu 305m  	2628	Mrežni kabl UTP Cat6 Cu Pakovanje 305m Plava boja Motalica.	0,375	0,360
MREŽNI KABL UTP Cat5E OUTDOOR CCAG 305m  	3490	Mrežni kabl UTP Cat5 CCAG za spoljnu montažu (outdoor), pakovanje 305m,motalica,crni.	0,300	0,250
MREŽNI KABL UTP Cat6E OUTDOOR CCAG 305m  	4266	Mrežni kabl UTP Cat6 CCAG za spoljnu montažu (outdoor), pakovanje 305m,motalica,crni.	0,360	0,300
MREŽNI KABL UTP Cat5E CCAG + SAJLA 305m  	3201	Mrežni kabl UTP Cat5 CCAG + SAJLA pakovanje 305m,motalica,crni.	0,387	0,330
MREŽNI KABL UTP Cat6E CCAG + SAJLA 305m  	3202	Mrežni kabl UTP Cat6 CCAG + SAJLA pakovanje 305m,motalica,crni.	0,576	0,480

NAPAJANJA I DC KONEKTORI

NAZIV ARTIKLA		Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
<u>NAPAJANJE</u>					
<u>XED-1212S</u>		1633	12W / 1A / 12V	6,00	5,00
<u>NAPAJANJE</u>					
<u>XED-2012S</u>		1382	24W / 2A / 12V	7,20	6,00
<u>NAPAJANJE</u>					
<u>XED-3013S</u>		1383	36W / 3A / 12V	11,16	9,30
<u>NAPAJANJE</u>					
<u>XED-5013S</u>		1384	60W / 5A / 12V	14,48	12,07
<u>NAPAJANJE</u>					
<u>XED-6013B</u>		3509	72W / 6A / 12V	17,22	14,35
<u>NAPAJANJE</u>					
<u>XED-RZ120200GJ</u>		4895	24W / 2A / 12V Ulazni Naponi: 100-240VAC	9,60	8,00
<u>9-KANALNO NAPAJANJE</u>					
<u>XED10A12VX-9L</u>		5435	120W / 10A / 12V	67,20	56,00
<u>18-KANALNO NAPAJANJE</u>					
<u>XED-15A12VX-18CH</u>		5114	180W / 15A / 12V	86,40	72,00
<u>DC KABL-MUŠKI</u>					
	1387	DC utikač-muški		0,48	0,40
<u>DC KABL-ŽENSKI</u>					
	5044	DC utikač-ženski		0,48	0,40
<u>DC KONEKTOR MUŠKI</u>					
	3425	DC konektor Muški		0,83	0,69
<u>DC KONEKTOR ŽENSKI</u>					
	4197	DC konektor ženski.		0,83	0,69
<u>DC RAZDELNIK 1-4</u>					
	1388	1 DC utičnica - 4 DC utikača		1,99	1,66
<u>DC RAZDELNIK 1-8</u>					
	1389	1 DC utičnica - 8 DC utikača		3,97	3,31
<u>TRAFO ZA NAPAJANJE KAMERA</u>					
	1935	24 V AC / 70 VA		28,98	24,15

PREKIDAČKA NAPAJANJA

NAZIV ARTIKLA	Kat.br.	Karakteristike	Cena (racun bez PDV)	Cena -20%
<u>NAPAJANJE</u> <u>XED-2812T</u> 	4896	Snaga: 30W Ulazni Naponi: 90 - 264V AC Izlazni Napon: 12V 2,5A Dimenzije: 115x50x30mm	8,40	7,00
<u>NAPAJANJE</u> <u>XED-5A12VWT-XK</u> 	4897	Snaga: 60W Ulazni Naponi: 100 - 240V AC Izlazni Napon: 12V 5A Dimenzije: 104x96x35.5mm	16,80	14,00
<u>NAPAJANJE</u> <u>XED-10A12VWT</u> 	4898	Snaga: 120W Ulazni Naponi: AC100-120V/200-240V Izlazni Napon: 12V 10A Dimenzije: 159x97.5x38mm	31,20	26,00
<u>NAPAJANJE</u> <u>XED-15A12VWT</u> 	4899	Snaga: 180W Ulazni Naponi: AC100-120V/200-240V Izlazni Napon: 12V 15A Dimenzije: 159x98x41.5mm	34,80	29,00
<u>NAPAJANJE</u> <u>XED-20A12VWT</u> 	4900	Snaga: 240W Ulazni Naponi: AC100-120V/200-240V Izlazni Napon: 12V 20A Dimenzije: 215x115x50mm	38,40	32,00
<u>NAPAJANJE</u> <u>XED-30A12VWT</u> 	4901	Snaga: 360W Ulazni Naponi: AC100-120V/200-240V Izlazni Napon: 12V 30A Dimenzije: 215x115x50mm	54,00	45,00